

Atlona AT-HDR-EX-70-2PS 4K HDR HDMI Over HDBaseT Extender (Transmitter/Receiver) Kit

Video				
HD/SD	4096x2160@24/25/30/50/60Hz*, 3840x2160@24/25/30/50*/60Hz*, 2048x1080p, 1080p@23.98/24/25/29.97/30/50/59.94/60Hz, 1080i@50/59.94/60Hz, 720p@50/59.94/60Hz, 576p, 576i, 480p, 480i			
VESA	2560x2048, 2560x1600, 2048x1536, 1920x1200, 1680x1050, 1600x1200, 1600x900, 1440x900, 1400x1050, 1366x768, 1360x768, 1280x1024, 1280x800 1280x768, 1152x768, 1024x768, 800x600, 640x480			
Color Space	YUV, RGB			
Chroma Subsampling	4:4:4, 4:2:2, 4:2:0*			
Color Depth	8-bit, 10-bit, 12-bit			
Audio				
Formats	PCM 2Ch, LPCM 5.1, LPCM 7.1, Dolby® Digital, DTS 5.1, Dolby Digital Plus, Dolby TrueHD, DTS-HD Master Audio™, Dolby Atmos®, DTS:X			
Sample Rate	32 kHz, 44.1 kHz, 48 kHz, 88.2 kHz, 96 kHz, 176.4 kHz, 192 kHz			
Bit Rate	24-bit (max.)			
Resolution / Distance	4K/UHD - Feet / Meters		1080p - Feet / Meters	
HDMI	15	5	30	10
CAT5e/6	115	35	200	60
CAT-6a / CAT-7	130	40	230	70
Signal				
Bandwidth	10.2 Gbps			
CEC	Yes			
HDCP	2,2			
Temperature	Fahrenheit		Celsius	
Operating	32 to 122		0 to 50	
Storage	-4 to 140		-20 to 60	
Humidity (RH)	20% to 90%, non-condensing			
Power				
Consumption	TBD			
Idle Consumption	TBD			
Supply	Input: 100 - 240 V AC, 50/60 Hz Output: 5 V DC			
Dimensions	Inches		Millimeters	
HxWxD	1.00 x 4.30 x 3.00		25 x 109x76	