

INPUTS

1 HDMI: On a female HDMI connector

OUTPUTS

1 HDMI: On a female HDMI connector

PORTS

1 USB: On a female mini USB connector

VIDEO

Max Resolution: 4K@60Hz (4:2:0)

Max Data Rate: 10.2Gbps (3.4Gbps per data channel)

Compliance: HDMI, HDCP 1.4

USER INTERFACE

Indicators: HDMI In, HDMI Out, Power LEDs

Controls: 8 DIP–switches

POWER

Source: 5V DC

Consumption: 315mA

ENVIRONMENTAL CONDITIONS

Operating Temperature: 0° to +40°C (32° to 104°F)

Storage Temperature: –40° to +70°C (–40° to 158°F)

Humidity: 10% to 90%, RHL non–condensing

ENCLOSURE

Cooling: Convection

Type: Aluminum

Size: PicoTools®

REGULATORY COMPLIANCE (STANDARDS COMPLIANCE)

Vibration: ISTA 1A in carton (International Safe Transit Association)

Safety: CE

Environmental: RoHs, WEEE

ACCESSORIES

Included: Power supply, bracket kit

PRODUCT DIMENSION

6.22cm x 5.18cm x 2.44cm (2.45" x 2.04" x 0.96") W, D, H

PRODUCT WEIGHT

0.1kg (0.2lbs) approx.

SHIPPING DIMENSION

15.70cm x 12.00cm x 8.70cm (6.18" x 4.72" x 3.43") W, D, H

SHIPPING WEIGHT

0.6kg (1.3lbs) approx.
