



## Introduction

The Atlona **AT-UHD-SW-510W** is a 5x2, multi-format matrix switcher with wireless presentation capability. It provides universal BYOD (bring your own device) compatibility with HDMI, DisplayPort, and USB-C inputs, plus wireless connectivity for mobile devices. The SW-510W is HDCP 2.2 compliant, and features matrixed or mirrored HDMI and HDBaseT outputs. The HDBaseT output is ideal for use with the Atlona AT-UHD-EX-100CE-RX-PSE HDBaseT receiver, or the AT-HDVS-SC-RX scaling HDBaseT receiver. It also includes automatic input switching and automatic display control capability, both applicable to wired and wireless source connections. This unique multi-format matrix switcher and wireless gateway provides a universal connectivity solution for presentation devices in a wide range of professional AV applications.

## Applications

- Meeting spaces**  
 The SW-510W provides the flexibility to accept any presenter device, whether wired or wireless. This capability is ideal for a wide range of meeting environments, from a huddle room to a large presentation space in a convention center.
- Classrooms and auditoriums**  
 A credenza or lectern-based AV system for resident sources, plus wireless connectivity for a participant's laptop or tablet.
- Small to medium-sized meeting spaces**  
 The SW-510W is compact and ideal for under-table mounting. It conveniently provides automatic switching and display control for simplified user operation, especially with laptops and mobile devices brought into the system.
- Conference rooms and boardrooms**  
 The SW-510W features two matrixed outputs for seamless integration into a display and a hardware-based videoconferencing system, with additional versatility by enabling wireless AV content presentations to the far end. The matrix switching capability provides the convenience of auto-switching for local BYOD content that feeds into the codec, while simultaneously allowing far-end content to be shared.
- Presentation spaces where two displays are needed**  
 This switcher can be installed in a lectern to serve a confidence monitor, plus the primary display in a remote location. With matrixed outputs, the SW-510W also can support two simultaneous presenters on two screens.

## Key Features

### 5x2 universal AV matrix switcher

- Two HDMI, one DisplayPort, and one USB-C\* input, plus a dedicated wireless AV input.
- Delivers true BYOD capability for a wide range of presentation sources.

### Matrixed or mirrored HDMI and HDBaseT outputs

- HDBaseT output transmits AV, control, and Ethernet up to 330 feet (100 meters) @ 1080p with CAT5e/6 or 4K/UHD using CAT6a/7 cable.
- Mirrored 18 Gbps HDMI and 10 Gbps HDBaseT outputs provide flexible options for AV system designs and applications.

### Wireless AV gateway

- Provides convenient Wi-Fi connectivity for an iOS, Android†, Mac, Chromebook, or Windows-based device.
- Includes dual Wi-Fi access points – secondary access point required for Miracast (Wi-Fi Direct).
- Integrated access point can be segregated from the facility network for security reasons.

### Native platform-based, wireless interfacing

- Allows screen mirroring without the need for a separate app.
- Supports wireless video up to 1080p/30 4:2:0 (up to 1080p/60 with Miracast).§
- Supports Bluetooth®-assisted iOS device discovery. An optional Bluetooth adapter is required (not included with the SW-510W). The Plugable and Kinivo Bluetooth 4.0 adapters are recommended.
- Also supports Miracast over Infrastructure for use of facility Wi-Fi or Ethernet network.

### Automatic input selection and automatic display control

- Automatically changes display power state, and switches between inputs based on device connection or disconnection from the switcher.
- Works for both wired and wireless source devices.
- Enables effortless, automated system operation without the need for an external control system.

\* USB-C port supports AV and device charging, but not USB data.

† Does not support casting of video from apps such as YouTube, Netflix, Hulu, and Amazon Prime Video.

- When an input is routed to one of the two available outputs, auto-switching remains available for the remaining inputs.

### USB-C charging for laptops, tablets, and smartphones

- Conveniently provides mobile device powering during a meeting or presentation.
- Simple one-cable connection for AV and charging.

### 4K/UHD capability @ 60 Hz with 4:2:0 chroma subsampling, plus support for 4K/60 4:4:4 and HDR formats on local ports (HDMI, USB-C, and DisplayPort)

- Ideal for new and emerging 4K/UHD and HDR-capable sources and displays.
- Compatible with 4K HDR10 and Dolby® Vision™ @ 60 Hz.
- Recommended HDBaseT receiver: AT-UHD-EX-100CE-RX-PSE.

### Occupancy sensor triggering

- When used with a third-party occupancy sensor, the switcher can wake from standby, power up the display, and deliver a welcome screen when someone walks into the room.
- Greatly simplifies user operation by avoiding the need to manually power up the system.

### TCP/IP, RS-232, and contact closure control

- Ideal for IP-based control from Atlona Velocity Control System and the AT-ANC-108D button control panel.
- Also compatible with third-party control systems.
- Contact closure control ideal for room functions such as motorized screens and display lifts, as well as occupancy sensing and remote button controls.

### Award-winning 10 year limited product warranty

- Ensures long-term product reliability and performance in commercial and residential systems.
- Specify, purchase, and install with confidence.

§ Video resolution capability is dependent on wireless signal quality.

## Specifications

Video	
HDMI	2.0 <sup>(1)</sup>
HDCP	2.2 (wired-device connections, only)
UHD/HD	4096x2160 @ 60 <sup>(2)</sup> /50/30/25/24 Hz 3840x2160 @ 60 <sup>(2)</sup> /50/30/25/24 Hz 1920x1080p @ 60/59.9/50/30/29.97/25/24/23.98 Hz 1920x1080i @ 30/29.97/25 Hz 1280x720p @ 60/59.94/50 Hz 720x576p @ 50 Hz 720x576i @ 50 Hz 640x480p @ 60/59.96 Hz 640x480i @ 30 Hz
VESA All resolutions are 60 Hz	2560x1600 2048x1536 1920x1200 1680x1050 1600x1200 1440x900 1400x1050 1280x1024 1280x800 1366x768 1360x768 1152x864 1024x768 800x600 640x480
USB-C <sup>(3)</sup>	Up to 4K/UHD @ 60 Hz for devices supporting USB-C Alternate Mode video output
Wireless	Up to 1080p @ 30 Hz 4:2:0 (up to 1080p @ 60 Hz with Miracast™); dependent on wireless signal quality
Color Space	YUV, RGB
Chroma Subsampling	4:4:4, 4:2:2, 4:2:0
Color Depth	8-bit, 10-bit, 12-bit
HDR <sup>(4)</sup>	HDR10, Hybrid-Log Gamma (HLG), and Dolby® Vision™ @ 60 Hz

Audio	
HDMI / HDBaseT Pass-Through Formats	LPCM 2.0 Dolby® Digital Dolby Digital Plus™ Dolby TrueHD Dolby Atmos® DTS® Digital Surround™ DTS-HD Master Audio™ DTS:X®
Bit Rate	24 Mbits/s max
<b>Analog Audio</b>	
Format	2-channel stereo
Balanced Output	+4 dBu, nominal gain; +20 dBu headroom
Frequency Response	20 Hz to 20 kHz, ±0.5 dB
THD + N	< 0.009% @ 20 Hz to 20 kHz
SNR	> 94 dB @ 1 kHz, zero clipping @ 0 dBFS, unweighted
Sample Rate	32 kHz, 44.1 kHz, 48 kHz, 88.2 kHz, 96 kHz, 176.4 kHz, 192 kHz

USB	
Signal	2.0
Maximum Data Rate	120 Mbps
USB-C	Supports Audio, Video, device and host data, and up to 60W power charging
USB-C Device Charging Capability	Up to 20 V, 3 A Output: 60 W @ 20 V, 36 W @ 12 V, 15 W @ 5 V

Protocols	
Addressing	DHCP, static
Security	HTTPS, SSL, TLS
Authentication	IEEE 802.1x
Wi-Fi	IEEE 802.11n/ac 2.4 GHz / 5 GHz
Wi-Fi Security	WPA, WPA2, PSK

Control	
RS-232	Device control and configuration; supports baud rates from 2400 to 115200 Bidirectional pass-through from control system to network
TRIGGER	Occupancy sensor triggering; wake from standby and/or display power-up when room becomes occupied.
RELAY	Contact closure control for room functions such as motorized screens and display lifts, as well as occupancy sensing and remote button controls.

Resolution / Distance	4K/UHD - Feet / Meters		1080p - Feet / Meters	
HDMI IN/OUT	15	5	30	10
CAT5e	230	70	330	100
CAT6/6a/7	330	100	330	100

Connectors	
HDMI IN	2 - Type A, 19-pin female
HDMI OUT	1 - Type A, 19-pin female
DP IN	1 - 20-pin female
USB-C IN	1 - USB Type-C v3.1, 24-pin female, AV input (Alternate Mode)
USB	3 - USB 2.0 Type A for Wi-Fi® antenna modules
RS-232	1 - 3-pin captive screw (bidirectional)
RELAY	1 - 3-pin captive screw, normally open (NO), with adjustable Toggle and Pulse modes; Electrical rating: 48 V @ 1 A
TRIGGER	1 - 4-pin captive screw, supports 3 - 30 V DC input range, power supply is 12 V @ 100 mA max.
AUDIO IN	1 - 3.5 mm, unbalanced 2-channel
AUDIO OUT	1 - 5-pin captive screw, balanced / unbalanced 2-channel
HDBaseT OUT	1 - RJ45
LAN	1 - RJ45, 10/100/1000 Mbps
DC 24V	1 - 4-pin DIN, locking

### Indicators and controls

USB-C	1 - LED, blue
DP	1 - LED, blue
HDMI 3	1 - LED, blue
HDMI 4	1 - LED, blue
BYOD	1 - LED, blue
Control Buttons	4 - momentary, tact-type  INPUT: Switches between inputs IP: Displays the IP address of the unit on the connected display POWER: Power-off the unit DISPLAY: Power-on / power-off the connected display

### Environmental

Operating Temperature	+32 to +122 °F 0 to +50 °C
Storage Temperature	-4 to +140 °F -20 to +60 °C
Operating Humidity (RH)	20% to 95%, non-condensing

### Power

Consumption (full load)	121 W
Idle Consumption	35 - 40 W
Supply	Input: 100 - 240 V AC, 50/60 Hz Output: 24 V / 5 A DC

Dimensions (H x W x D)	Inches	Millimeters
Unit	1.73 x 8.46 x 10.19	44 x 215 x 259
Power Supply (AT-PS-48208-D3) <sup>(5)</sup>	1.6 x 2.6 x 6.2	40.6 x 66 x 157.4

Weight	Pounds	Kilograms
Device	3.70	1.68

### Certification

Device	CE, RoHS, FCC
--------	---------------

## Accessories

SKU	Description
AT-UHD-SW-510W-RM	AT-UHD-SW-510W Rack Mount

## Footnotes

- (1) 18 Gbps supported for HDMI 2.0 output. HDBaseT output limited to 10 Gbps.
- (2) HDMI output supports 4K/UHD @ 50 or 60Hz with 4:4:4 chroma sampling. HDBaseT output supports 4K/UHD @ 50 or 60Hz with 4:2:0 chroma subsampling.
- (3) USB-C does not support the following input resolutions: 2560x2048, 2048x1536, 2028x1080, and 1440x1050.
- (4) HDR not supported on HDBaseT output.
- (5) Revision A hardware uses AT-PS-245-C power supply. Revision B hardware uses AT-PS-245-D4 power supply. Power supply dimensions are the same.

## Copyright, Trademark, and Registration

© 2021 Atlona Inc. All rights reserved. "Atlona" and the Atlona logo are registered trademarks of Atlona Inc. Pricing, specifications and availability subject to change without notice. Actual products, product images, and online product images may vary from images shown here.



The terms HDMI, HDMI High-Definition Multimedia Interface, and the HDMI Logo are trademarks or registered trademarks of HDMI licensing Administrator, Inc.



Dolby, Dolby Atmos, and the double-D symbol are registered trademarks of Dolby Laboratories Licensing Corporation.



For DTS patents, see <http://patents.dts.com>. Manufactured under license from DTS, Inc. DTS, the Symbol, DTS and the Symbol together, and Digital Surround are registered trademarks and/or trademarks of DTS, Inc. in the United States and/or other countries. © DTS, Inc. All Rights Reserved.

All other trademark(s), copyright(s), and registered technologies mentioned in this document are the properties of their respective owner(s).