

AG Neovo HX-24 24in SEMI RUGGED VGA/DVI/HDMI/SDI LCD DISPLAY/LED PANEL/SPEAKERS

		HX-22	HX-24
Panel	Panel Size	21.5'	23.6'
	Max. Resolution	FHD 1920 x 1080	FHD 1920 x 1080
	Pixel Pitch	0.2480 mm	0.2715 mm
	Brightness	250 cd/rrF	250 cd/nrF
	Contrast Ratio	3.000 (Typical)	3.000 (Typical)
	Viewing Angle (???)	88*/ 88* (Typical)	178/178* (Typical)
	Display Colour	16.7M	16.7M
	Response Time	3ms (GTG)	5ms (GTG)
	Frequency (???)	H: 24 kHz - 82 kHz V: 50 Hz - 85 Hz	H: 24 kHz - 82 kHz V: 50 Hz - 85 Hz
Input	VGA	15-Pin D-Sub	15-Pin D-Sub
	DVI	24-Pin DVI-D	24-Pin DVI-D
	CVBS	BNC x 1	BNC x 1
	SDI	BNC x 1	BNC x 1
	HDMI	HDMI x 1	HDMI x 1
Output	CVBS	BNC x 1	BNC x 1
	SDI	BNC X 1	BNC X 1
Audio	Audio Input	1 x stereo audio in for PC (audio jack. 3.5 0) 1 x stereo audio in for CVBS	1 x stereo audio in for PC (audio jack. 3.5 0) 1 x stereo audio in for CVBS
	Speaker Out	2W x 2	2W x 2
Power In	External Adaptor	AC 100-240V. 50-60HZ	AC 100-240V. 50-60HZ
	DC Jack F2.1	DC 12V	DC 12V
	Consumption	< 22W (On)	< 27W (On)
		< 0.5W (Stand-by) < 0.5W (Off)	< 0.5W (Stand-by) < 0.5W (Off)
Operating Conditions	Temperature	0 *C - 40 *C (32 *F - 104 *F)	0 *C - 40 *C (32 *F - 104 *F)
	Humidity	10%-90%	10% - 90%
Storage Conditions	Temperature	-20 *C-60*C (-4 *F - 140 *F)	-20 *C-60 *C (-4 *F- 140 *F)
	Humidity	5% - 95%	5% - 95%
Weight	Without Base	6.3 kg (13.9 lbs)	7.2 kg (15.9 lbs)
	With Base	6.8 kg (15.0 lbs)	7.7 kg (17.0 lbs)