

## AG Neovo RX-42 42in SEMI RUGGED LCD DISPLAY/ VGA/DVI/HDMI/BNC LOOP THROUGH

Item		RX-32	RX-42
LCD panel	Active area (H x V mm)	698.4 x 392.85	927.94x521.96
	Pixel pitch (mm)	0.3637 x 0.3637	0.4833 x 0.4833
	Native resolution (pixels)	1920x1080	
	Brightness (cd/m2) (typical)	350	400
	Contrast (typical)	3000:1	1000:1
	Adaptive contrast	14700:1	33500:1
	Response time (ms) (typical)	6,5	9
Input	Computer	VGA (D-Sub 15-pin)	
	Video	DVI (DVI-D). Composite Video (BNC jack). S-Video. YPbPr (RCA jacks). HDMI x 2. DisplayPort	
	Audio	UR (RCA jacks). Line-in (3.5 mm jack)	
	Control	RS-232C (D-Sub 9-pin). RJ45 (Jack RJ45 W/LED I)	
Output	Computer	VGA (D-Sub 15-pin)	
	Video	DVI (DVI-D). Composite Video (BNC jack)	
	Speaker	External speaker jack (10W+10W. 8 Ohms)	External speaker jack (12W+12W. 8 Ohms)
	Audio	UR (RCA jacks)	
	Control	RS-232C (D-Sub 9-pin)	
Power	Supply	100-240V AC. 50/60 Hz	
	Consumption Max.	< 85 W < 150 W	
	Consumption Standby	< 0.5 W	
Environment	Operating Temperature	0 - 40°C, 32- 104°F	
	Operating Humidity	10 - 90% (without condensation)	
	Storage Temperature	-20 - 60°C. 4 - 140°F	
	Storage Humidity	10 - 95% (without condensation)	
	Display Orientation	Landscape/Portrait	
Mechanical	Weight (lbs/kg)	36.38/16.5 (Approximately)	55.66/25.7 (Approximately)
	Dimensions (WxHxD) (inch/mm)	29.8x17.8x2.73/ 756.6 x 451.1 x 94.8	38.6 x 22.6 x 4.8/ 980x574x121