

Apantac HDBT-SET-11 4K/UHD HDMI/HDBaseT Extender (Transmitter/Receiver) Set with RS-232/IR up to 230ft/70m

HDBT-1-E-UHD

MODEL	HDBT-1-E-UHD
DESCRIPTION	Single-port HDBaseT HDMI Extender
HDMI Connectors	1 x HDMI Type A (Female)
RJ-45 Connectors	1 x RJ-45
RS-232 Connectors	1 x DB9 (female)
IR In	1 x 3.5 mm stereo jack
IR out	1 x 3.5 mm stereo jack
DIP Switch	1 x 3 Pin
LED Indicators	1 x 4 in 1 LED
Maximum Resolution	4K/UHD@60Hz 4:4:4
Maximum Distance	230 ft (70 meters) for 4K/UHD 60Hz / 490 ft (150 meters) for 4K/UHD 30Hz or 1080P60Hz
Power	DC 12V 1.5 A with locking
Weight	300 g
Dimension	126 x 83 x 25 mm

HDBT-1-R-UHD

MODEL	HDBT-1-R-UHD
DESCRIPTION	Single-port HDBaseT HDMI Receiver
HDMI Connectors	1 x HDMI Type A (Female)
RJ-45 Connectors	1 x RJ-45
RS-232 Connectors	1 x DB9 (female)
IR In	1 x 3.5 mm stereo jack
IR out	1 x 3.5 mm stereo jack
DIP Switch	1 x 3 Pin
LED Indicators	1 x 4 in 1 LED
Maximum Resolution	4K/UHD@60Hz 4:4:4
Maximum Distance	230 ft (70 meters) for 4K/UHD 60Hz / 490 ft (150 meters) for 4K/UHD 30Hz or 1080P60Hz
Power	DC 12V 1.5 A with locking
Weight	300 g
Dimension	126 x 83 x 25 mm