

Apantac KVM-SET-14 KVM/HDMI Extender (Transmitter/Receiver) Set over IP with Looping Input and POE

Products		KVM-IP-Tx-PL	KVM-IP-Rx-P
Video	Input	HDMI	RJ45
	Output	HDMI	HDMI
	Input	3.5 mm Stereo Phone Jack	3.5 mm Stereo Phone Jack
	Output	3.5 mm Stereo Phone Jack	N/A
Microphone	Input	N/A	3.5 mm Stereo Phone Jack
USB	Tx Side	USB Type B (Female)	N/A
	Rx Side	N/A	4 x USB Type A (Female)
System Link	Input	N/A	RJ45
	Output	RJ45	N/A
RS-232 Baud Rate	3-pin Pheonix Connector / up to 115,200 bps / Full Duplex		3-pin Pheonix Connector / up to 115,200 bps / Full Duplex
Video Resolution	Maximum 4K/UHD@30Hz		Maximum 4K/UHD@30Hz
Interconnect Cable	Standard CAT6/CAT6a/CAT7 network cable		Standard CAT6/CAT6a/CAT7 network cable
Maximum Cable Length	170m point to point, 100m when connected to a switch		170m point to point, 100m when connected to a switch
Temperatures	Operating Temperature: 0 ~ 50 C, Storage Temperature: -20 ~ 85C		Operating Temperature: 0 ~ 50 C, Storage Temperature: -20 ~ 85C
Enviromental Humidity	0 ~ 80% (non-consensing)		0 ~ 80% (non-consensing)
Power / Weight / Dimension	DC 12V, 1.5A. Consumption 400 mA, 600g. 153.4 x 88.2 x 31.5 mm		DC 12V, 1.5A. Consumption 400 mA, 600g. 153.4 x 88.2 x 31.5 mm