

Soundtube RS1001i-II-T-WH 10in Coaxial Open-Ceiling Speaker/53 Hz-175 kHz/White

System Type	10-inch subwoofer, openceiling, ported (150watt transformer for 25/70.7/100-volt or transformer bypass applications)
Impedance (nominal)1	4 ohm
Sensitivity dB @ 2.83 V/l m	86.0 dB
Sensitivity dB @ 1 W/l m2	83.0 dB
Frequency Response (- 3 dB)3	53 Hz-175Hz
Frequency Response (-10 dB)3	38 Hz-450 Hz
Max. Program Power4	300 W
Max. Continuous Power RMS5	150 W
Max. Power SPL @ 1 m 6	105.0 dB
Tap Selector	Five-position rotary switch with transformer bypass
Transducer - Low-Frequency Driver	254 mm (10 in.) polypropylene cone, butyl rubber surround
Low-Frequency Voice Coil	35.0 mm/1.38 in.
Network Type: Low-Pass	6 dB per octave, 1st order
Network Type: High-Pass	N/A
Enclosure Material	Injection-molded ABS, glass fiber reinforced
Grille	Powder coated steel
Inputs	Four-pin, 5.08 mm Euroblock for individual or daisy chain connection
Colors	Black or white
Height	437.6 mm (17.23 in.)
Diameter	376.4 mm (14.82 in.)
Weight	12.3 kg (27.0 lbs)
Shipping Weight	14.8 kg (32.5 lbs)
Included accessories	Hanging hardware, Euroblock connector, terminal weather boot
Optional accessories	Surfacemount bracket (AC-RSSM8)
Packaging	One per box
Regulatory - UL	1480 (UEAY) and 2239-approved
Regulatory - CE	Approved
RoHS	Approved