

Gefen EXT-4K600A-MF-51-HBTL5 4K Ultra HDMI/DisplayPort/VGA 600 MHz Multi-Format 5x1 Scaler with Auto-Switching/HDBaseT Outputs

- Recommended HDBaseT™ Receiver: EXT-UHDA-HBTL-RX
- Maximum Input TMDS Clock/Bandwidth: 600 MHz/18 Gbps
- Maximum Output TMDS Clock/Bandwidth: 300 MHz/10.2 Gbps
- Video Input Connectors:
 - (3) HDMI Type A 19-pin, locking, female
 - (1) DisplayPort™ 20-pin, female
 - (1) VGA HD-15, female
- Video Output Connectors:
 - (1) HDMI Type A 19-pin, locking, female
 - (1) HDBaseT™ RJ-45, shielded
- L/R Unbalanced Analog Audio Input ports: (5) 3-pin Phoenix with removable plug
- L/R Balanced/Unbalanced Mic/Line Input port: (1) 3-pin Phoenix with removable plug
- L/R Analog Unbalanced Audio Output port: (1) 3-pin Phoenix with removable plug
- Input Control port: (1) 6-pin Phoenix with removable plug
- RS-232 port: (1) 3-pin Phoenix with removable plug
- IR In/Ext port: (1) 3.5mm mini-stereo jack
- IR Extender type: EXT-RMT-EXTIRN
- IR Output port: (1) 3.5mm mini-mono jack
- IR Remote Battery: (1) Lithium (CR2025)
- Firmware Update port: (1) USB Type-A, female
- Input Select Switches: (5) tact-type, with Blue LED indicator backlight
- Auto-Switching On/Off Switch: (1) tact-type, with Blue LED indicator backlight
- Power On/Off Switch: (1) tact-type, with Blue LED indicator backlight
- Mic/Line Configuration Switch: (1) 3-position slide-type
- Power Supply Connector: (1) 5.5mm barrel/2.1mm pin, Locking
- Power Supply: (1) 12V DC, locking, 5.5mm barrel/2.1mm pin
- Power Consumption:
 - Not powering a Receiver: 12W maximum
 - Powering a Receiver: 24W maximum
- Operating Temperature: +32 to +122 °F (0 to +50 °C)
- Operating Humidity: 5% to 90% RH, non-condensing
- Storage Temperature: -4 to +185 °F (-20 to +85 °C)
- Storage Humidity: 0% to 95% RH, non-condensing
- MTBF: 50000 hours
- Dimensions (W x H x D, not including the connectors): 8.8" x 1.75" x 6.25" (223mm x 44mm x 158mm)
- Net Weight: 2.5 lbs. (1.2 kg)
- Shipping Weight: 4.0 lbs. (1.8kg)