

Bolide BTG1209IRODVA/28AHQ-4 Set of 4 2.0 MP HD Analog IR Bullet Camera with 2.8-12mm Lens Kit

Parameter Classification	Parameter Name	BTG1209IRODVA/28AHQ Parameter Value
Camera	Image Sensor	1/2.9" 2MP Progressive Scan COMS
	Resolution	1920*1080
	Image System	PAL/NTSC
	Minimum Illumination	Color: 0.08 lux @ (F1.2, AG C ON), 0 lux with IR
	Electronic shutter	PAL: 1/25 s to 1/50,000 s; NTSC: 1/30 s to 1/50,000 s
	Lens	2.8-12mm Manual variable focal Lens
	SMD	24 PCS Minicrystal Led
	SNR	>52dB (AGC off)
	IR distance	40m
	Video Frame Rate	1080P@25fps, 1080P@30fps
	Video Output	1HD TVI/AHD/CVI/CVBS output
Menu	D&N	Support ICR EXT/Auto / Color/ BW (Black and White)
	White Balance	ATW / MWB
	BLC	Support
	Image set	Brightness, sharpness, digital noise reduction,color,Saturation
	Language	English, Chinese
General	Power Supply	12VDC± 10%;
	Operating Conditions	(-20° C to 60° C), Humidity 90% or less (non-condensing)
	Protection level	IP66
	Power Consumption	Max. 6W with IR cut filter on
	Dimensions	118mm*118mm*83.6mm