

RDL D-TPR2A Active 2-Pair Extender (Receiver)/Format-A/stereo jack out

Input:	RDL FORMAT-A
Input Connection:	RJ45 (Models D-, DS-); Detachable Terminal Block (Model EM-)
Format-A Signal Pairs Used (2):	B (Left); C (Right)
Format-A Output:	RJ45 (not applicable to EM-)
Output:	100 Ω unbalanced
Output Connection:	RCA Phono
Frequency Response:	10 Hz to 50 kHz (\pm 0.1 dB)
THD+N:	< 0.005%
Noise below -4 dBu:	< -90 dB
Crosstalk:	< 90 dB (1 kHz); <75 dB (20 Hz to 20 kHz)
Headroom above +4 dBu:	> 18 dB
CMRR:	> 80 dB (50 Hz to 150 Hz)
Indicator:	Power In
Power Connections (2):	Detachable terminal block; RJ45
Ambient Operating Environment:	0° C to 55° C
Power Requirement:	24 Vdc @ 45 mA plus connected loads
Dimensions:	1.6" (4.06 cm) W; 4.11" (10.45 cm) H; 1.89" (4.8 cm) D
Mounting Box Minimum Depth:	2.4" (Models D-, DS-); 39 mm (Model EM-)
Package Type:	Cardboard Box
Package Dimensions:	3.625 x 4.625 x 2.125 In.
Shipping Weight:	0.395 lbs.
WEEE weight:	0.245 lbs.
Tariff code:	8517.18.0000