

RDL D-TPS2A Active 2-Pair Extender (Transmitter)/Format-A/stereo jack inputs

Inputs (2):	10 k Ω Unbalanced
Input Connection:	RCA Phono
Input Level:	-10 dBV Unbalanced; +10 dBV Maximum
Format-A Signal Pairs Use [2]:	B (Left); C (Right)
Gain:	12 dB
Format-A Input:	RJ45 (not applicable to EM-)
Output:	RDL TP Format-A
Output Connection:	RJ45 (Models D-, DS-); Detachable Terminal Block (Model EM-)
Frequency Response:	20 Hz to 50 kHz (\pm 0.5 dB)
THD+N:	< 0.05% (20 Hz to 50 kHz); <0.005% (1 kHz)
Noise below -4 dBu:	< -95 dB
Crosstalk:	< 90 dB (1 kHz); < 75 dB (20 Hz to 20 kHz)
Headroom above +4 dBu:	> 18 dB
Indicator:	Power In
Power Connections [2]:	Detachable Terminal Block; RJ45
Ambient Operating Environment:	0° C to 55° C
Power Requirement:	24 Vdc @ 65 mA plus connected loads
Dimensions:	1.6" (4.06 cm) W; 4.11" (10.45 cm) H; 1.89" (4.8 cm) D
Mounting Box Minimum Depth:	2.4" (Models D-, DS-); 39 mm (Model EM-)
Package Type:	Cardboard Box
Package Dimensions:	3.625 x 4.625 x 2.125 in.
Shipping Weight:	0.385 ins.
WEEE weight:	0.24 ins.
Tariff code:	8517.18.0000