

RDL D-TPS8A Format-A Multiple Location Audio Extender (Transmitter)

Inputs (2):	10 k Ω Unbalanced, stereo; Format-A
Input Connection:	Mini jack (front panel); RJ45 (rear panel)
Input Level:	-10 dBV; +10 dBV Maximum
Format-A Signal Pairs Used (2):	B (Left); C (Right)
Gain:	12 dB
Output:	RDL TP Format-A
Output Connection:	RJ45
Frequency Response:	20 Hz to 50 kHz (\pm 0.5 dB)
THD+N:	< 0.1% (20 Hz to 50 kHz); <0.01% (1 kHz)
Noise below +4 dBu:	< -85 dB; < -75 dB with up to 10 -TPS8A modules connected
Crosstalk:	< 85 dB (1 kHz); < 75 dB (20 Hz to 20 kHz)
Headroom above +4 dBu:	> 20 dB
Power Connection:	RJ45
Ambient Operating Environment:	0° C to 55° C
Power Requirement:	24 Vdc @ 30 mA
Dimensions:	1.33" (3.37 cm) D; 1.72" (4.37 cm) W; 4.11" (10.44 cm) H
Package Type:	Cardboard Box
Package Dimensions:	3.625 x 4.625 x 2.125 in.
Shipping Weight:	0.405 lbs.
WEEE Weight:	0.26 lbs