

RDL FP-AVDA4 1x4 Stereo Audio/Video Distributor/Phono Jacks

Input:	Phono jack, 1V p-p
Input Impedance:	75 Ω
Gain:	Unity
Outputs (4):	Phono jack
Output Level:	1 V p-p (into 75 Ω)
Frequency Response:	10 Hz to 10 MHz (\pm 0.2 dB)
Noise:	< -75 dB (below 1 V p-p)
Output Isolation:	> 45 dB
Differential Gain:	0.1%
Differential Phase:	0.1 degree (measured at 10% and 90% APL)
AUDIO	
Inputs (2):	Phono jacks (stereo), -10 dBV Unbalanced
Input Impedance:	10 Ω , bridging
Gain:	Unity
Outputs (8):	Phono jacks (4 stereo)
Output Impedance:	150 Ω drives 10 Ω lines
Frequency Response:	20 Hz to 40 kHz (\pm 0.25 dB)
THD+N:	< 0.05%; typ. 0.01% (1 kHz)
IMD:	< 0.02%
Output Level:	-10 dBV
Headroom:	> 18 dB
Noise:	< -85 dB below -10 dBV
Crosstalk:	Better than 75 dB (20 Hz to 20 kHz); typ < -90 dB (1 kHz)
Ambient Operating Environment:	0° C to 55° C
Power Requirement:	GROUND-REFERENCED, 24 Vdc @ 60 mA
Dimensions:	Height: 1.20 in. 3.05 cm; Width: 3.25 in. 8.26 cm; Length: 6.41 in.16.23 cm
Package Type:	Cardboard Box
Package Dimensions:	4.375 x 7 x 2.25 in.
Shipping Weight:	0.39 5 lbs.
WEEE weight:	0.65 lbs.
Tariff code:	8518.40.2000