

Shinybow SB-5616 16x2 HDMI Routing Selector Switch (both outputs mirrored)

- Type of HDMI Switcher: 16x HDMI inputs To 2x HDMI Outputs Routing Switcher
- HDMI Support: HD 1080p-@60Hz, H36-bit Deep color, 3D (1.4a) formats.
- HDCP / CEC Support: HDCP 2.0 Compliant, CEC Compliant.
- Video Bandwidth: Double Data Rates:225Mhz, Total 3.75Gbps bandwidth.
- Digital Video Support: Full HD resolution : 480i / 480p / 720p / 1080i / 1080p
- Digital Audio Support: Multi Audio Formats 5.1 / 7.1, MAT(MLP), Dolby Digital, Dolby TrueHD, Dolby Digital Plus, DTS, DTS-ES 6.1, DTS-HD, DTS-HD-HRA, DTS-HD Master, (PCM-2CH)
- Controls:
 - IR Remote Controller
 - IR External port x 1 (OD 3.5mm Ear phone Jack)
 - Select & Function buttons on front panel
 - RS-232 series interface
- Double Output: Support output #2 port simultaneously via Output #1
- Infrared Frequency: 38 Khz
- IR External Distance: ~1000 feet / 300 meters maximum
- HDMI I/O Connector: HDMI Type A - SMD 19pin Female Type
- Temperature: 32 °F - 100 °F Operation (0 °C - 38 °C)
- Size (WxDxH): 19 x 9.85 x 1.75 in (482x250x44mm)
- Rack Mount: Rack Mount 1RU High 19" Rack Mount (with rack mount)
- Power Supply: DC12V / 3A, Universal world wide Type 50/60Hz, 100~230 VAC
- Power Consumption: 1850 mA Maximum
- Safety Approvals: CE, FCC, RoHS (2002/95/EC).
- Net Weight: 2.15 Kgs / 3.58 lb