

Kramer PA-240Net 240W Networked Power Amplifier

INPUTS

- 2 Channels, on a Dante™ Net: On an RJ-45 connector
- 1 Balanced Stereo Audio: +4dBu/10kΩ, on a 5 pin terminal block

OUTPUTS

- 1 Balanced Stereo Audio: Line level, on a 5-pin terminal block
- 1 Speaker: On a 4-pin large terminal block

PORTS

- 1 Control via IP: On an RJ-45 connector
- 1 RS-232: On a 3-pin terminal block

AMPLIFIER

- Input Sensitivity: Full power @ 0.3V (–10dBV)
- Output Power: 2 x 120W @ 4Ω or 8Ω, 1 x 240W @ 70V or 100V
- Class: D
- Maximum Voltage Gain: 26dB SE / 32dB BTL
- Dynamic Range: 119dB
- Frequency Response: 20Hz to 20kHz @ +/-1dB
- S/N Ratio: 80dB, 20Hz — 20kHz
- Audio THD + Noise: THD+N (1kHz @ 1W) 0.003 %
- Audio 2nd Harmonic: 0.08% @ 75W RMS @ 4Ω 6.67kHz

USER INTERFACE

- Controls: Output volume attenuator, IP and RS-232

POWER

- Source: Universal mains operational voltage 85V AC — 265V AC (full power at 120V — 230V)
- Consumption: 265VA
- Total System Efficiency: 90%

ENVIRONMENTAL CONDITIONS

- Operating Temperature: 0° to +40°C (32° to 104°F)
- Storage Temperature: –40° to +70°C (–40° to 158°F)
- Humidity: 10% to 90%, RHL non-condensing

REGULATORY COMPLIANCE (STANDARDS COMPLIANCE)

- Safety: CE, FCC
- Environmental: RoHs, WEEE

ENCLOSURE

- Size: ½ 19” desktop
- Type: Aluminum
- Cooling: Convection ventilation

ACCESSORIES

- Included: Power cord

PRODUCT DIMENSION

- 21.46cm x 16.30cm x 4.36cm (8.45" x 6.42" x 1.72") W, D, H

PRODUCT WEIGHT

- 1.1kg (2.3lbs) approx.

SHIPPING DIMENSION

- 40.50cm x 29.70cm x 9.00cm (15.94" x 11.69" x 3.54") W, D, H

SHIPPING WEIGHT

- 1.7kg (3.6lbs) approx.