

KanexPro HDMX44-18G 4x4 HDMI 2.0 Matrix Switcher with 4K/60Hz

VideoBandwidth	600MHz/18Gbps
InputPorts	4 x HDMI 1 x IR 1 x RS-232 1 x MiniUSB (Service) 1 xRJ45 (Control)
OutputPorts	4 x HDMI
Supported Resolutions:	480i ~1080p@24/50/60Hz 4K up to 4096x2160@60Hz (YUV 4:4:4,8-bit) PC resolutions: VGA~WUXGA
IR Frequency	30~50kHz
BaudRate	115200bps
PowerSupply	24V DC/2.7A (US/EU standards,CE/FCC/ ULcertified)
ESD Protection	Human body model: ±8 kV (air-gapdischarge) ±4 kV (contactdischarge)
Dimensions	17.0" x 1.7"x 6.2" (436 mm x 44 mm x 160mm WxHxD) [CaseOnly] 17.0" x 1.8" x 6.60" (436 mm x 48 mm x167.5mm WxHxD) [All Inclusive]
Weight	4.55 lbs. (2068g)
Chassis Material	Metal
Color	Black
OperatingTemperature	0°C~40°C/32°F~104 F
Storage Temperature	-20°C~60°C/-4°F~140 F
Relative Humidity	20~90% RH(non-condensing)
PowerConsumption	21 Watts

* Please check manual under downloads tab for more advanced spec information.