

# KanexPro WP-2X1HDUSBC 4K/60 3x1 HDMI 2.0/USB-C HDBaseT 2xGang Wallplate Switcher/Extender (Transmitter) with IR/PoH

<b>Input</b>	
Input	(2) HDMI, (1) USB-C (Slimport)
Input Connector	(2) Type-A female HDMI, (1) Type-C USB
HDMI Input Resolution	Up to 4K@60Hz 4:4:4
Slimport Input Resolution	Up to 4K@30Hz 4:4:4
<b>Output</b>	
Output	(1) HDBT OUT
Output Connector	(1) RJ45
HDBT Output Resolution	Up to 4K@60Hz 4:4:4
<b>Control</b>	
Control Ports	(1) IR, (1) FIRMWARE, (1) RS232, (1) IR IN
Control Connector	(1) Built-in IR sensor, (1) Micro-USB, (1) 3-pin terminal block, (1) 2-pin terminal block
<b>General</b>	
Bandwidth	18Gbps
Transmission Mode	HDBaseT
HDMI Version	2.0
HDCP Version	2.2
Transmission Distance	4K@60Hz = 40M, 1080P@60Hz = 70M
External Power Supply	Input:100V~240V AC; Output: 24VDC 1.25A
Power Consumption	22W (Max)
Operation Temperature	-10°C ~ +55°C
Storage Temperature	-25°C ~ +70°C
Relative Humidity	10% ~ 90%
Dimension (W*H*D)	3.5' x 4.0" x 1.7"
Net Weight	0.62 lbs. (285g)