

# KanexPro WP-HDBTKVM3 4K60 2xGang HDMI/USB 2.0 HDBaseT Wall Plate Switcher/Extender (Transmitter/Receiver) Set with IR/PoH

<b>Input</b>	
Input	(2) HDMI
Input Connector	(2) Type-A female HDMI
<b>Output</b>	
Output	(1) HDBT, (1) TO PC, (1) DC OUT
Output Connector	(1) RJ45, (1) Type-B USB, (1) 2-pin terminal block
<b>Control</b>	
Control Ports	(1) FIRMWARE, (1) RS232
Control Connector	(1) Micro-USB, (1) 3-pin terminal block
<b>General</b>	
Bandwidth	10.2Gbps
HDMI Version	1.4
HDCP Version	2.2
Video Resolution	Up to 4Kx2K@60Hz 4:2:0
Transmission Mode	HDBaseT
Transmission Distance	1080p/4K@60Hz = 328ft/100m
Power Supply	Powered from the receiver by CATx cable.
Operation Temperature	-10°C ~ +55°C
Storage Temperature	-25°C ~ +70°C
Relative Humidity	10% ~ 90%
Dimension (W*H*D)	3.5" x 4.0" x 1.7"
Net Weight	0.55 lbs (250g)