

## Aten PE0212G Basic PDU Series/16A Max/100-240 VAC

Function	PE0212A	PE0212B	PE0212G
<b>Electrical</b>			
Nominal Input Voltage	100-120 VAC	100-240 VAC	100-240 VAC
Maximum Input Current	20A Max (UL de-rated 16A Max)	20A (Max) (UL de-rated 16A Max)	16A (Max)
Input Frequency	50-60 Hz	50-60 Hz	50-60 Hz
Input Connection	For A Plug NEMA L5-20P For A2 Plug : INEMA 5-20P	NEMA L6-20P	IEC-320 C20
Input Power	2400VA(MAX) 1920VA(UL de-rated)	4800VA(Max); 3840VA(UL de-rated)	3840VA(Max)
Outlet Type	(12) NEMA 5-20R	(12) IEC 320 C13	(12) IEC 320 C13
Maximum Output Current (Outlet)	20A (Max) (UL de-rated 16A Max)	15A (Max) (UL de-rated 12A Max)	10A (Max)
Maximum Output Current (Bank)	20A (Max) (UL de-rated 16A Max)	20A (Max) (UL de-rated 16A Max)	16A (Max)
Maximum Output Current (Total)	20A (Max) (UL de-rated 16A Max)	20A (Max) (UL de-rated 16A Max)	16A (Max)
OPD(Overcurrent Protection Device)	Yes	Yes	Yes
<b>Physical Properties</b>			
Dimensions (L x W x H)	48.80 x 4.40 x 4.50 cm (19.21 x 1.73 x 1.77 in.)	48.80 x 4.40 x 4.50 cm (19.21 x 1.73 x 1.77 in.)	48.80 x 4.40 x 4.50 cm (19.21 x 1.73 x 1.77 in.)
Weight	0.88 kg ( 1.95 lb )	0.88 kg ( 1.95 lb )	0.88 kg ( 1.95 lb )
Power Cord Length	10ft(12#)	10ft(12#)	10ft(3×1.5mm2)
<b>Environmental</b>			
Temperature (Operating / Storage)	0 - 40°C / -20 - 60°C *When the environmental temperature comes close 40 degrees, it is recommended to lower the load to 60% to comply to the safety regulations.	0 - 40°C / -20 - 60°C *When the environmental temperature comes close 40 degrees, it is recommended to lower the load to 60% to comply to the safety regulations.	0 - 40°C / -20 - 60°C *When the environmental temperature comes close 40 degrees, it is recommended to lower the load to 60% to comply to the safety regulations.
Elevation (Operating / Storage)	3000m	3000m	3000m
<b>Compliance</b>			
EMC Verification	FCC Class A	FCC Class A	CE Class A
Safety Verification	TBD	TBD	CE, LVD
Note	For some of rack mount products, please note that the standard physical dimensions of WxDxH are expressed using a LxWxH format.		