Aten VC081 True 4K HDMI EDID Emulator

Power Power status (Green x 1) Status Learning (Blue x 1) Video Input Interfaces 1 x HDMI Type A Male (Black) Impedance 100 Ω Video Output Interfaces 1 x HDMI Type A Female (Black) Impedance 100 Ω Video Video HDMI 2.0 (3D, Deep Color) HDCP 2.2 Compatible Consumer Electronic Control (CEC) EDID Settings EDID Mode: Default / Learning Connectors Power Consumption Bus-powered (5 VDC from source device) Power Consumption 240MWBTU Environmental Operating Temperature 0 - 50 °C C Storage Temperature -20 - 60 °C C Humidity 0 - 80% RH, Non-Condensing Physical Properties Housing Plastic (ABS) Weight 0.01 kg (0.02 lb) Dimensions (L x W x 4.40 x 2.40 x 1.18 cm H) (1.73 x 0.94 x 0.46 in.) Carton Lot 40 pcs Note For some of rack mount products, please note that the standard physical dimensions of WXDXH are expressed using the properties and p	LEDs	
Status Learning (Blue x 1) Video Input Interfaces		
Video Input Interfaces 1 x HDMI Type A Male (Black) Impedance 100 Ω Video Output Interfaces 1 x HDMI Type A Female (Black) Impedance 100 Ω Video Video Video Video Video Video HDMI 2.0 (3D, Deep Color) HDCP 2.2 Compatible Consumer Electronic Control (CEC) EDID Settings EDID Mode: Default / Learning Connectors Power Bus-powered (5 VDC from source device) Power Consumption 240MWBTU Environmental Operating Temperature Video O- 50 °C Temperature Video Vid		
Interfaces 1 x HDMI Type A Male (Black) Impedance 100 Ω Video Output Interfaces 1 x HDMI Type A Female (Black) Impedance 100 Ω Video Video Video HDMI 2.0 (3D, Deep Color) HDCP 2.2 Compatible Consumer Electronic Control (CEC) EDID Settings EDID Mode: Default / Learning Connectors Power Bus-powered (5 VDC from source device) Power Consumption 240MWBTU Environmental Operating Temperature 2-0 - 60 °C Temperature 4-10 - 80 °C Hunidity 0 - 80 °C RH, Non-Condensing Physical Properties Housing Plastic (ABS) Weight 0.01 kg (0.02 lb) Dimensions (L x W x 4.40 x 2.40 x 1.18 cm H) (1.73 x 0.94 x 0.46 in.) Carton Lot 40 pcs Note		Learning (Blue x 1)
Impedance 100 Ω Video Output Interfaces 1 x HDMI Type A Female (Black) Impedance 100 Ω Video Compliance HDMI 2.0 (3D, Deep Color) HDCP 2.2 Compatible Consumer Electronic Control (CEC) EDID Settings EDID Mode: Default / Learning Connectors Power Bus-powered (5 VDC from source device) Power Consumption 240MWBTU Environmental Operating Temperature 0 - 50 °C Storage Temperature20 - 60 °C Humidity 0 - 80% RH, Non-Condensing Physical Properties Housing Plastic (ABS) Weight 0.01 kg (0.02 lb) Dimensions (L x W x 4.40 x 2.40 x 1.18 cm H) (1.73 x 0.94 x 0.46 in.) Carton Lot 40 pcs Note For some of rack mount products, please note that the standard physical dimensions of WxDxH are expressed usin	Video Input	
Video Output Interfaces 1 x HDMI Type A Female (Black) Impedance 100 Ω Video Compliance HDMI 2.0 (3D, Deep Color) HDCP 2.2 Compatible Consumer Electronic Control (CEC) EDID Settings EDID Mode: Default / Learning Connectors Power Bus-powered (5 VDC from source device) Power Consumption 240MWBTU Environmental Operating Temperature 0 - 50 °C Storage Temperature -20 - 60 °C Humidity 0 - 80% RH, Non-Condensing Physical Properties Housing Plastic (ABS) Weight 0.01 kg (0.02 lb) Dimensions (L x W x / 4.40 x 2.40 x 1.18 cm / H) (1.73 x 0.94 x 0.46 in.) Carton Lot 40 pcs Note For some of rack mount products, please note that the standard physical dimensions of WxDxH are expressed usin	Interfaces	1 x HDMI Type A Male (Black)
Interfaces 1 x HDMI Type A Female (Black) Impedance 100 Ω Video Compliance HDMI 2.0 (3D, Deep Color) HDCP 2.2 Compatible Consumer Electronic Control (CEC) EDID Settings EDID Mode: Default / Learning Connectors Power Bus-powered (5 VDC from source device) Power Consumption 240MWBTU Environmental Operating Temperature 0 - 50 °C Storage Temperature - 20 - 60 °C Temperature 14 Unidity 0 - 80% RH, Non-Condensing Physical Properties Housing Plastic (ABS) Weight 0.01 kg (0.02 lb) Dimensions (L x W x 4.40 x 2.40 x 1.18 cm H) (1.73 x 0.94 x 0.46 in.) Carton Lot 40 pcs Note	Impedance	100 Ω
Impedance 100 Ω Video Compliance HDMI 2.0 (3D, Deep Cotor) HDCP 2.2 Compatible Consumer Electronic Control (CEC) EDID Settings EDID Mode: Default / Learning Connectors Power Bus-powered (5 VDC from source device) Power Consumption 240MWBTU Environmental Operating Temperature 0 - 50 °C Storage Temperature - 20 - 60 °C Temperature Ununidity 0 - 80% RH, Non-Condensing Physical Properties Housing Plastic (ABS) Weight 0.01 kg (0.02 lb) Dimensions (L x W x 4.40 x 2.40 x 1.18 cm H) (1.73 x 0.94 x 0.46 in.) Carton Lot 40 pcs Note	Video Output	
Video Compliance HDMI 2.0 (3D, Deep Color) HDCP 2.2 Compatible Consumer Electronic Control (CEC) EDID Settings EDID Mode: Default / Learning Connectors Power Bus-powered (5 VDC from source device) Power Consumption 240MWBTU Environmental Operating Temperature 0 - 50 °C Storage Temperature - 20 - 60 °C Humidity 0 - 80% RH, Non-Condensing Physical Properties Housing Plastic (ABS) Weight 0.01 kg (0.02 lb) Dimensions (L x W x 4.40 x 2.40 x 1.18 cm (1.73 x 0.94 x 0.46 in.) Carton Lot 40 pcs For some of rack mount products, please note that the standard physical dimensions of WxDxH are expressed usin	Interfaces	1 x HDMI Type A Female (Black)
HDMI 2.0 (3D, Deep Color) Compliance HDCP 2.2 Compatible Consumer Electronic Control (CEC) EDID Settings EDID Mode: Default / Learning Connectors Power Bus-powered (5 VDC from source device) Power Consumption 240MWBTU Environmental Operating Temperature 0 - 50 °C Storage Temperature -20 - 60 °C Humidity 0 - 80% RH, Non-Condensing Physical Properties Housing Plastic (ABS) Weight 0.01 kg (0.02 lb) Dimensions (L x W x	Impedance	100 Ώ
Compliance HDCP 2.2 Compatible Consumer Electronic Control (CEC) EDID Settings EDID Mode: Default / Learning Connectors Power Bus-powered (5 VDC from source device) Power Consumption 240MWBTU Environmental Operating Temperature 0 - 50 °C Storage Temperature - 20 - 60 °C Humidity 0 - 80% RH, Non-Condensing Physical Properties Housing Plastic (ABS) Weight 0.01 kg (0.02 lb) Dimensions (L x W x H, A) x 2.40 x 1.18 cm (1.73 x 0.94 x 0.46 in.) Carton Lot 40 pcs Note	Video	
EDID Settings	Compliance	HDCP 2.2 Compatible
Connectors Power Bus-powered (5 VDC from source device) Power Consumption 240MWBTU Environmental Operating Temperature 0 - 50 °C Storage Temperature20 - 60 °C Humidity 0 - 80% RH, Non-Condensing Physical Properties Housing Plastic (ABS) Weight 0.01 kg (0.02 lb) Dimensions (L x W x 4.40 x 2.40 x 1.18 cm H) (1.73 x 0.94 x 0.46 in.) Carton Lot 40 pcs Note	EDID Settings	
Power Consumption 240MWBTU Environmental Operating Temperature 0 - 50 °C Storage Temperature - 20 - 60 °C Humidity 0 - 80% RH, Non-Condensing Physical Properties Housing Plastic (ABS) Weight 0.01 kg (0.02 lb) Dimensions (L x W x 4.40 x 2.40 x 1.18 cm H) (1.73 x 0.94 x 0.46 in.) Carton Lot 40 pcs Note		
Environmental Operating Temperature 0 - 50 °C Storage Temperature -20 - 60 °C Humidity 0 - 80% RH, Non-Condensing Physical Properties Housing Plastic (ABS) Weight 0.01 kg (0.02 lb) Dimensions (L x W x 4.40 x 2.40 x 1.18 cm (1.73 x 0.94 x 0.46 in.)) Carton Lot 40 pcs For some of rack mount products, please note that the standard physical dimensions of WxDxH are expressed usin	Power	Bus-powered (5 VDC from source device)
Operating Temperature 0 - 50 °C Storage Temperature -20 - 60 °C Humidity 0 - 80% RH, Non-Condensing Physical Properties Housing Plastic (ABS) Weight 0.01 kg (0.02 lb) Dimensions (L x W x 4.40 x 2.40 x 1.18 cm H) (1.73 x 0.94 x 0.46 in.) Carton Lot 40 pcs For some of rack mount products, please note that the standard physical dimensions of WxDxH are expressed usin	Power Consumption	240MWBTU
Temperature Storage Temperature -20 - 60 °C Humidity 0 - 80% RH, Non-Condensing Physical Properties Housing Plastic (ABS) Weight 0.01 kg (0.02 lb) Dimensions (L x W x 4.40 x 2.40 x 1.18 cm (1.73 x 0.94 x 0.46 in.)) Carton Lot 40 pcs For some of rack mount products, please note that the standard physical dimensions of WxDxH are expressed using the product of the standard physical dimensions of WxDxH are expressed using the product of the standard physical dimensions of WxDxH are expressed using the product of the standard physical dimensions of WxDxH are expressed using the product of the standard physical dimensions of WxDxH are expressed using the product of the standard physical dimensions of WxDxH are expressed using the product of the product of the standard physical dimensions of WxDxH are expressed using the product of the produ	Environmental Environmental	
Temperature Humidity 0 - 80% RH, Non-Condensing Physical Properties Housing Plastic (ABS) Weight 0.01 kg (0.02 lb) Dimensions (L x W x 4.40 x 2.40 x 1.18 cm (1.73 x 0.94 x 0.46 in.) Carton Lot 40 pcs For some of rack mount products, please note that the standard physical dimensions of WxDxH are expressed usin		0 - 50 ºC
Physical Properties Housing Plastic (ABS) Weight 0.01 kg (0.02 lb) Dimensions (L x W x 4.40 x 2.40 x 1.18 cm H) (1.73 x 0.94 x 0.46 in.) Carton Lot 40 pcs Note For some of rack mount products, please note that the standard physical dimensions of WxDxH are expressed usin		-20 - 60 ºC
Housing Plastic (ABS) Weight 0.01 kg (0.02 lb) Dimensions (L x W x 4.40 x 2.40 x 1.18 cm (1.73 x 0.94 x 0.46 in.) Carton Lot 40 pcs Note For some of rack mount products, please note that the standard physical dimensions of WxDxH are expressed usin	Humidity	0 - 80% RH, Non-Condensing
Weight 0.01 kg (0.02 lb) Dimensions (L x W x 4.40 x 2.40 x 1.18 cm H) (1.73 x 0.94 x 0.46 in.) Carton Lot 40 pcs For some of rack mount products, please note that the standard physical dimensions of WxDxH are expressed usin	Physical Properties	
Dimensions (L x W x 4.40 x 2.40 x 1.18 cm H) (1.73 x 0.94 x 0.46 in.) Carton Lot 40 pcs Note For some of rack mount products, please note that the standard physical dimensions of WxDxH are expressed usin	Housing	Plastic (ABS)
H) (1.73 x 0.94 x 0.46 in.) Carton Lot 40 pcs For some of rack mount products, please note that the standard physical dimensions of WxDxH are expressed usin	Weight	0.01 kg (0.02 lb)
Note For some of rack mount products, please note that the standard physical dimensions of WxDxH are expressed usin	-	
INOTE	Carton Lot	40 pcs
a LXWXTI IOIIIIat.	Note	For some of rack mount products, please note that the standard physical dimensions of WxDxH are expressed using a LxWxH format.