

ClearView HD4-B150 4MP Bullet 3.6mm 265ft Night Vision Smart IR WDR

Camera	
Image Sensor	1/3" CMOS
Effective Pixels	2688(H)×1520(V), 4.1MP
Scanning System	Progressive
Electronic Shutter Speed	1/3s~1/300,000s
Minimum Illumination	0.03Lux/F1.5, 0Lux IR on
S/N Ratio	More than 65dB
IR Distance	265 feet
IR On/Off	Control Auto / Manual
IR LEDs	2
Lens	
Lens Type	Fixed lens / Fixed iris
Mount Type	Board-in
Focal Length	3.6mm
Max Aperture	F1.5
Angle of View	H: 78°
Focus Control	N/A
Close Focus Distance	1500mm 59.06"
Pan / Tilt / Rotation	
Pan/Tilt/Rotation	Pan: 0° ~ 360° Tilt: 0° ~ 87° Rotation: 0° ~ 360° Manual Adjustments
Video	
Resolution	4MP (2560×1440)
Frame Rate	25fps@4MP, 25/30fps@1080P, 25/30fps@720P
Video Output	1-channel BNC HD-AVS high definition video output
Day/Night	Auto (ICR) / Manual
OSD Menu	Multi-language
BLC Mode	BLC / HLC / WDR
WDR	120dB
Gain Control	AGC
Noise Reduction	2D/3D
White Balance	Auto / Manual
Smart IR	Auto / Manual
Certifications	
Certifications	CE (EN55032, EN55024, EN50130-4) FCC (CFR 47 FCC Part 15 subpartB, ANSI C63.4-2014) UL (UL60950-1+CAN/CSA C22.2 No.60950-1)
Electrical	
Power Supply	12V DC ±25%
Power Consumption	Max 7W (12V DC, IR on)
Environmental Operating Conditions	-22°F ~ +140°F / Less than 90% RH * Start up should be done at above -22°F
Storage Conditions	-22°F ~ +140°F / Less than 90% RH Ingress Protection & Vandal Resistance IP-67
Construction Casing	Aluminium
Dimensions	9.52"×3.56"×3.56"
Net Weight	1.41lbs
Gross Weight	1.70lb