

## AG Neovo TX-19 19in IP65 front-sided 10-point touch display

Panel	Panel Type Panel Size Max. Resolution Pixel Pitch Brightness Contrast Ration Viewing Angle (H/V) Disply Colour Response Time (GTG)	LED-Backlit TFT LCD 19.0" 1280 x 1024 0.294 mm 250 cd/m2 (Typical) 1000 : 1 (Typical) 170°/160° 16.7 M 3 ms (GTG)
Frequency (H/V)	H.Freq V.Freq	31.5kHz - 80kHz 56Hz - 75Hz
Input	VGA DVI	15-Pin D-Sub 24-Pin DVI-D
External Control	RJ11	RJ11
Touch Screen	Technology Positioning Accuracy Active Force Panel Interface	Projected Capacitive ±2.5mm Non-required USB (Type-B, HID compliant)
Power	Power Supply Power Requirements Consumption	External DC 12V < 22W (On) < 2W (Stand-by) < 1W (Off)
Operating Conditions	Temperature Humidity	0°C - 40°C (32°F-104°F) 10% - 80% (No condensation)
Storage Conditions	Temperature Humidity	-20°C - 60°C (-4°F-140°F) 10% - 90% (No condensation)
Mounting	VESA FPMPI	Yes (100 x 100mm)
Dimensions	with Base (W x D x H) w/o Base (W x H x D) Packaging (W x H x D)	427 x 375 x 214 mm (16.8" x 14.8" x 8.4") 427 x 355 x 49 mm (16.8" x 14.0" x 1.9") 500 x 295 x 460 mm (19.7" x 11.6" x 18.1")
Weight	Product Weight (with base) Packaging weight	6.5 kg (14.3 lbs) 8.3 kg (18.3 lbs)
Regulation Approval	Certifications & Compliance	CE, RoHS, WEEE, REACH
Accessories	Supplied	CD ROM (user manual and touch driver), 15-Pin D-Sub cable, power cord, power adaptor, USB cable, cable cover and screw, warranty card