

## AG Neovo LW-24 24 inch LED Display/Full HD/HDMI Inputs

<b>Panel</b>	Panel Type	LED-backlit TFT LCD
	Panel Size	24.0" / 23.6"
	Max. Resolution	Full HD 1920 x 1080
	Pixel Pitch	0.277 mm / 0.272 mm
	Brightness	250 cd/m2 (Typical)
	Contrast Ratio	20,000,000:1 (DCR)
	Surface Treatments	Hard Coating (3H), Anti-glare treatment
	Viewing Angle (H/V)	170°/160° (Typical)
	Display Colour	16.7M
	Response Time	3 ms (GTG)
<b>Frequency (H/V)</b>	H.Freq	30 kHz - 83 kHz
	V.Freq	56 Hz - 75Hz
<b>Input</b>	Analogue	15-Pin D-Sub
	Digital	24-Pin DVI-D
	HDMI	HDMI
<b>Audio</b>	Audio In	3.5mm Audio Line-in
	Speaker	2W x 2
<b>Power</b>	Power Supply	Internal
	Power Requirements	AC 100 – 240 V, 50-60 Hz
	Consumption	< 33W (On) / < 0.5W (Stand-by) / < 0.5W (Off)
<b>Plug &amp; Play</b>	VESA	DCC 2B
<b>Operating Conditions</b>	Temperature	0°C ~ 40°C
	Humidity	10% ~ 85%
<b>Storage Conditions</b>	Temperature	-25°C ~ 55°C
	Humidity	10% ~ 85%
<b>Mounting</b>	VESA FPMPMI	Yes (100 x 100mm)
<b>Tilt</b>	Tilt	-4° ~ +18°
<b>Dimensions</b>	Product	566 x 395 x 190 mm
	(W x H x D)	(22.3" x 15.6" x 7.5")
	Packaging	622 x 423 x 130 mm
	(W x H x D)	(24.5" x 16.7" x 5.1")
<b>Weight</b>	Product Weight	4.3 kg (9.5 lbs) / 3.6 kg (7.9 lbs)
	Packaged Product Weight	5.7 kg (12.5 lbs) / 5.2 kg (11.5 lbs)
<b>Regulation Approval</b>	Certifications & Compliance	FCC, CE, BSMI, GOST-R, WEEE, RoHs, REACH
<b>Accessories</b>	Supplied	CD ROM (user manual), 15-Pin D-Sub cable, audio cable, AC power cord