

# AG Neovo HX-32 32 inch LED-Backlit Display/Optical Glass/SDI Inputs

<b>Panel</b>	Panel Type	LED-Backlit TFT LCD (MVA panel)
	Panel Size	31.5"
	Max. Resolution	1920 x 1080
	Pixel Pitch	0.3637 mm
	Brightness	500 cd/m2 (Typical)
	Contrast Ratio	3,000:1 (Typical)
	Viewing Angle (H/V)	178°/178° (Typical)
	Display Colour	16.7M
	Response Time	4 ms (GTG)
<b>Frequency (H/V)</b>	H.Freq	30 kHz - 75 kHz
	V.Freq	50 Hz - 75Hz
<b>Input</b>	VGA	15-Pin D-Sub
	DVI	24-Pin DVI-D
	S-Video	4-Pin mini DIN
	Component (YPbPr)	RCA
	HDMI	HDMI x 2
	SDI	BNC
	CVBS	BNC
	DisplayPort	DisplayPort
<b>Out</b>	VGA	15-Pin D-Sub
	DVI	24-Pin DVI-D
	SDI	BNC
	CVBS	BNC
<b>External Control</b>	RS-232 in/out	9-Pin D-Sub
	RJ45	RJ45
<b>Audio</b>	Audio In	1 x stereo audio in for PC (audio jack, 3.5 Ø) 1 x stereo audio in (RCA)
	Audio Out	1 x stereo audio out (RCA)
	Internal Speaker	10W x 2
	External Speaker Out	10W x 2
<b>SDI</b>	3G-SDI (SMPTE 424M)	1080p @50/60fps
	HD-SDI (SMPTE 292M)	720p @25/30/50/60fps 1080p @24/25/30/50/60fps 1080i @50/60fps
	SD-SDI (SMPTE 259M)	480i @60fps/576i @50fps
<b>Power</b>	Power Supply	Internal
	Power Requirements	100 ~ 240 V, 50 - 60 Hz
	Consumption	< 105W (On) / < 0.5W (Stand-by) / < 0.5W (Off)
<b>Sync Format</b>	Video System	NTSC/PAL
<b>Operating Conditions</b>	Temperature	0°C ~ 40°C (32°F~104°F)
	Humidity	10%~90% (No condensation)
<b>Storage Conditions</b>	Temperature	-20°C ~ 60°C (-4°F~140°F)
	Humidity	10%~90% (No condensation)
<b>Mounting</b>	VESA FPMPMI	Yes (400 x 200mm)

<b>Dimensions</b>	Product	757 x 451 x 95mm
	(W x H x D)	(29.8" x 17.8" x 3.7")
	Packaging	870 x 624 x 249mm
	(W x H x D)	(34.3" x 24.6" x 9.8")
<b>Weight</b>	Product Weight	15.2 kg (33.5 lbs)
	Packaged Product Weight	18.0 kg (39.7 lbs)
<b>Regulation Approval</b>	Certifications & Compliance	CE, RoHS, WEEE
<b>Accessories</b>	Supplied	CD ROM (user manual), 15-Pin D-Sub cable, power cord, remote control, batteries
	Optional	Stand base (STD-02)