

# AG Neovo SC-42 42 inch LED-Backlit Display

<b>Panel</b>	Panel Type	LED-Backlit TFT LCD (MVA panel)
	Panel Size	42"
	Max. Resolution	FHD 1920 x 1080
	Pixel Pitch	0.485 mm
	Brightness	400 cd/m2 (Typical)
	Contrast Ratio	3,000:1 (Typical)
	Viewing Angle (H/V)	178°/178° (Typical)
	Display Colour	16.7M
	Response Time	3 ms (GTG)
<b>Horizontal Resolution</b>	TV Lines	625TVL (NTSC) 650TVL (PAL)
<b>Frequency (H/V)</b>		H: 31.5 kHz - 80 kHz V: 50 Hz - 75 Hz
<b>Input</b>	Analogue	15-Pin D-Sub
	HDMI	HDMI
	CVBS	BNC x 1
	S-Video	4-Pin mini DIN
<b>Out</b>	CVBS	BNC x 1
<b>Audio</b>	Audio In	1 x stereo audio in for PC
	Audio Out	1 x stereo audio out
	Speaker	2W x 2
<b>Power</b>	Power Supply	Internal
	Power Requirements	100 ~ 240V, 50 - 60Hz
	Consumption	< 80 W (On)
<b>Plug &amp; Play</b>	VESA	EDID
<b>Operating Conditions</b>	Temperature	0 °C ~ 40 °C
	Humidity	10% - 85%
<b>Storage Conditions</b>	Temperature	-10 °C ~ 50 °C
	Humidity	10% ~ 95%
<b>Mounting</b>	VESA FPMPMI	Yes (400 x 400mm)
<b>Dimensions</b>	Product	992.3 x 656.3 x 240 mm
	(W x H x D)	(39.1" x 25.8" x 9.4")
	Packaging	1073 x 703 x 142 mm
	(W x H x D)	(42.2" x 27.7" x 5.6")
<b>Weight</b>	Product Weight	14.5 kg (32 lbs)
	Packaged Product Weight	16.5 kg (36.4 lbs)
<b>Regulation Approval</b>	Certifications & Compliance	CE, FCC, RoHs, WEEE
<b>Accessories</b>	Supplied	User manual, Base assembly installation guide, Remote control with AAA batteries, power cord, 15-Pin D-Sub cable & audio cable, screw package