

Key Digital KD-MVL4x2 4x2 MultiView Seamless HDMI Matrix Switcher w Ultra HD/4K

Technical:

- Inputs (each): 1 HDMI connector, Type A, 19 pin female; 1 HD analog video 15-pin female, 1 analog audio connector, 3.5mm stereo female
- Outputs (each): 1 HDMI connector, Type A, 19 pin female; 1 digital coaxial audio on RCA connector, female, follows SPDIF format IEC 60958
- TMDS Bandwidth: 9 Gb/s total
- Deep Color Support: Supports digital video formats in Deep Color Mode up to 12 bits/color with all HDMI and HDCP technologies
- Link: Single Link
- DDC Signal (Data): Input DDC signal – 5 Volts p-p (TTL)
- HDMI Video/Audio Signal: 1.2 Volts p-p
- DDC Communication: EDID And HDCP buffering between source and display
- Wired IR: Modulated IR signal input, 0-5V TTL or -10 to +10V, 3.5mm mono female connector with signal on tip
- Power: External power supply; 12V/3A

General:

- Regulation: CE, RoHS, WEEE
- Enclosure: Black metal
- Rack Mount: 1U, full rack-width (rack ears included)
- Accessories: Rack Ears, (6) HDMI Lacing Clips
- Product: 17.25" x 8.875" x 1.75"; Weight: 6.5 lbs
- Packaging: 18.5" x 13" x 3.5"; Weight: 8.8 lbs