

AG Neovo SC-32 32 inch LED-Backlit Display

Panel	Panel Type	LED-Backlit TFT LCD
	Panel Size	31.5"
	Max. Resolution	FHD 1920 x 1080
	Pixel Pitch	0.364 mm
	Brightness	450 cd/m2 (Typical)
	Contrast Ratio	3,000:1 (Typical)
	Viewing Angle (H/V)	178°/178° (Typical)
	Display Colour	16.7M
	Response Time	4 ms (GTG)
Horizontal Resolution	TV Lines	625TVL (NTSC) 650TVL (PAL)
Frequency (H/V)		H: 31.5 kHz - 80 kHz V: 50 Hz - 75 Hz
Input	Analogue	15-Pin D-Sub
	HDMI	HDMI
	CVBS	BNC x 1
	S-Video	4-Pin mini DIN
Out	CVBS	BNC x 1
Audio	Audio In	1 x stereo audio in for PC
	Audio Out	1 x stereo audio out
	Speaker	2W x 2
Power	Power Supply	Internal
	Power Requirements	100 ~ 240V, 50 - 60Hz
	Consumption	< 65 W (On)
Plug & Play	VESA	EDID
Operating Conditions	Temperature	0 °C ~ 40 °C
	Humidity	10% - 85%
Storage Conditions	Temperature	-10 °C ~ 50 °C
	Humidity	10% ~ 95%
Mounting	VESA FPMPMI	Yes (100 x 100mm)
Dimensions	Product	752.5 x 503.8 x 189 mm
	(W x H x D)	(29.6" x 21.2" x 7.4")
	Packaging	807 x 548 x 118 mm
	(W x H x D)	(31.8" x 21.6" x 4.6")
Weight	Product Weight	9.3 kg (20.5 lbs)
	Packaged Product Weight	10.2 kg (22.5 lbs)
Regulation Approval	Certifications & Compliance	CE, FCC, RoHs, WEEE
Accessories	Supplied	User manual, Base assembly installation guide, Remote control with AAA batteries, power cord, 15-Pin D-Sub cable & audio cable, screw package