

AG Neovo HX-42 42 inch LED-Backlit Display/Optical Glass/SDI Inputs

Panel	Panel Type	LED-Backlit TFT LCD (IPS panel)
	Panel Size	42.0"
	Max. Resolution	1920 x 1080
	Pixel Pitch	0.4833 mm
	Brightness	400 cd/m2 (Typical)
	Contrast Ratio	1000:1 (Typical)
	Viewing Angle (H/V)	178°/178° (Typical)
	Display Colour	16.7M
	Response Time	6 ms (GTG)
Frequency (H/V)	H.Freq	30 kHz - 75 kHz
	V.Freq	50 Hz - 75Hz
Input	VGA	15-Pin D-Sub
	DVI	24-Pin DVI-D
	S-Video	4-Pin mini DIN
	Component (YPbPr)	RCA
	HDMI	HDMI x 2
	SDI	BNC
	CVBS	BNC
	DisplayPort	DisplayPort
Out	VGA	15-Pin D-Sub
	DVI	24-Pin DVI-D
	SDI	BNC
	CVBS	BNC
External Control	RS-232 in/out	9-Pin D-Sub
	RJ45	RJ45
Audio	Audio In	1 x stereo audio in for PC (audio jack, 3.5 Ø) 1 x stereo audio in (RCA)
	Audio Out	1 x stereo audio out (RCA)
	Internal Speaker	12W x 2
	External Speaker Out	12W x 2
SDI	3G-SDI (SMPTE 424M)	1080p @50/60fps
	HD-SDI (SMPTE 292M)	720p @25/30/50/60fps 1080p @24/25/30/50/60fps 1080i @50/60fps
	SD-SDI (SMPTE 259M)	480i @60fps/576i @50fps
Power	Power Supply	Internal
	Power Requirements	100 ~ 240 V, 50 - 60 Hz
	Consumption	< 105W (On) / < 0.5W (Stand-by) / < 0.5W (Off)
Sync Format	Video System	NTSC/PAL
Operating Conditions	Temperature	0°C ~ 40°C (32°F~104°F)
	Humidity	10%~80% (No condensation)
Storage Conditions	Temperature	-20°C ~ 60°C (-4°F~140°F)
	Humidity	10%~90% (No condensation)
Mounting	VESA FPMPMI	Yes (400 x 200mm)
Dimensions	Product	980 x 574 x 121mm
	(W x H x D)	(38.6" x 22.6" x 4.8")
	Packaging	1122 x 723 x 284mm

	(W x H x D)	(44.2" x 28.5" x 11.2")
Weight	Product Weight	25.7 kg (56.5 lbs)
	Packaged Product Weight	29.3 kg (64.5 lbs)
Regulation Approval	Certifications & Compliance	CE, RoHS, WEEE
Accessories	Supplied	CD ROM (user manual), 15-Pin D-Sub cable, power cord, remote control, batteries
	Optional	Stand base (STD-03)