



SX-15P

A surveillance display integrated with Anti-Burn-in™ technology and NeoV™ Optical Glass for 24/7 security and control centre environments.

The SX-15P is a durable performance 15" display. With its AIP technology, the SX-15P is capable of delivering image clarity and supporting multi-video applications. Its passive looping feature additionally makes the SX-15P a suitable model for surveillance settings. On top of the power DC-out design for easy installation of security peripherals, the SX-15P is armed with metal casing and NeoV™ Optical Glass to protect the display from damage caused by 24/7 operations under multi-user security environments.

- > NeoV™ Optical Glass
- > Anti-Burn-in™ technology
- > AIP technology: PIP/ PBP, Freeze & 180° Image Rotation; 3D Comb Filter/ De-interlace/Noise Reduction
- > Horizontal resolution up to 620TVL(NTSC), 625TVL(PAL)
- > Versatile connectivity: BNC in/out x2, S-Video, VGA, DVI, Audio in/out
- > BNC video out passive looping
- > Power DC-out design to power connected peripherals
- > NTSC/PAL/SECAM video system support
- > EcoSmart Sensor automatically adjusts backlight according to ambient lighting condition
- > Built-in speakers (1.5W x 2)
- > Black-level alignment
- > Durable metal housing
- > VESA standard wall mount
- > Rigorous screening of the components for mission-critical 24/7 applications



NeoV™ Optical Glass - The most trusted hard glass protection available. Only on AG Neovo displays



SX-15P

Specifications

SX-15P

Panel	Panel Type	LED-Backlit TFT LCD
	Panel Size	15.0"
	Max. Resolution	XGA 1024 x 768
	Pixel Pitch	0.297 mm
	Brightness	350 cd/m ² (Typical)
	Contrast Ratio	700:1 (Typical)
	Viewing Angle (H/V)	170°/160° (Typical)
	Display Colour Response Time	16.7M 4 ms (GTG)
Horizontal Resolution	TV Lines	620TVL (NTSC), 625TVL (PAL)
Frequency (H/V)		H: 24 kHz - 81 kHz V: 50 Hz - 75 Hz
Input	VGA	15-Pin D-Sub
	DVI	24-Pin DVI-D
	CVBS	BNC x 2
	S-Video	4-Pin mini DIN
Output	CVBS	BNC x 2
	DC Output	12V/500mA, DC jack 2.5Ø
Audio	Audio In	1 x stereo audio in for PC 1 x stereo audio in for CVBS (RCA)/ S-Video
	Audio Out	1 x stereo audio out for CVBS (RCA)/ S-Video
	Speaker	1.5W x 2
Power	Power Supply	External
	Power Requirements Consumption	DC 12V < 17 W (On) / < 0.5 W (Off)
NeoV™ Optical Glass	Thickness	3.0 mm (0.18")
	Reflection Rate	< 2%
	Transmission Rate	> 96%
	Coating Hardness	> 8H
Plug & Play	VESA	DCC 2B, DCC/CI
Operating Conditions	Temperature	0°C ~ 40°C (32°F ~ 104°F)
	Humidity	10% ~ 90%
Storage Conditions	Temperature	-20°C ~ 60°C (-4°F ~ 140°F)
	Humidity	5% ~ 95%
Mounting	VESA FPM/PMI	Yes (100 x 100mm & 75 x 75mm)
Tilt		0° ~ +20°
Dimensions	Product (W x H x D)	380 x 359 x 155 mm (15.0" x 14.1" x 6.1")
	Packaging (W x H x D)	454 x 422 x 190 mm (17.9" x 16.6" x 7.5")
Weight	Product Weight	4.7kg (10.4lbs)
	Packaged Weight	6.3kg (13.9lbs)
Regulation Approval	Certifications & Compliance	CB, FCC, CE, WEEE, RoHS, REACH,
Accessories	Supplied	CD ROM (user manual), power cord, power adaptor, 15-Pin D-Sub cable, warranty card



NeoV™ Optical Glass protects against scratches, impacts and other physical damage



Anti-Burn-in™ technology prevents image sticking



Flexible image viewing options such as PIP/PBP, freeze, 180° image rotation



Durable metal casing for enhanced strength and secure mounting



Ultimate video versatility, including passive looping BNC video for multiple display connections

