

# AG Neovo DR17P 17in durable/high resolution 1280 x 1024 medical Display

Panel	Panel Type	LED-Backlit TFT LCD
	Panel Size	17.0" (432 mm)
	Max. Resolution	SXGA 1280 x 1024
	Pixel Pitch	0.264 mm
	Brightness	250 cd/m2 (Typical)
	Contrast Ratio	1000:1 (Typical)
	Viewing Angle (H/V)	170/160° (Typical)
	Display Colour	16.7M
	Response Time	3 ms (GTG)
Frequency (H/V)		H: 24 kHz - 82 kHz
		V: 50 Hz - 85 Hz
Input	Analogue	15-Pin D-Sub
	Digital	24-Pin DVI-D
	S-Video	4-Pin Mini DIN
	CVBS	RCA
Audio	Audio In	1 x stereo audio in for PC (audio jack, 3.5 0)
		1 x stereo audio in for CVBS or S-Video (RCA)
	Speaker	1.5W x 2
Power	Power Supply	External
	Power Requirements	DC 24V
	Consumption	< 19 W (On)
		< 1W (Stand-by)
		< 1W (Off)
NeoV™ Optical Glass	Thickness	3.0 mm (0.12")
	Reflection Rate	<1%
	Transmission Rate	> 96%
	Coating Hardness	>9H
Plug & Play	VESA	DCC 2B, DDC/CI
Operating	Temperature	0 °C - 40 °C
Conditions	Humidity	10% - 90%
Storage	Temperature	-20 °C - 60 °C
Conditions	Humidity	5% - 95%
Mounting	VESA FPMPI	Yes (100 x 100mm & 75 x 75mm)
Tilt	Tilt	0° - +20°
Weight	Product Weight Packaged Product Weight	w/ Base 6.1 kg (13.4 lb) w/o Base 5.3 kg (11.71b)
		8.45 kg (18.63 lb)
Regulation Approval	Certifications & Compliance	FCC, CE, WEEE, RoHS, REACH, EN60601-1, IEC60601-1, C-tick, GOST-R, BSMI
Accessories	Supplied	CD ROM (user manual), 15-Pin D-Sub cable, S-Video cable, power cord, power adaptor 5 m, audio cable
	Optional	Display handle (HDL-01), X-ray film positioner