



KRAMER

TP-583Txr

4K HDR HDMI Transmitter with RS-232 & IR
over Extended-Reach HDBaseT

| HDMI | HDBaseT | 4K/60 UHD (4:4:4)



TP-583Txr is a high-performance, extended-reach HDBaseT transmitter for 4K HDR HDMI, RS-232 and IR signals over twisted pair. TP-583Txr converts all input signals into the transmitted HDBaseT signal. It enables extending video signal up to 100m (330ft) at 4K@60Hz (4:4:4) video resolution, up to 180m (590ft) at 4K@60Hz (4:2:0), and up to 200m (650ft) at HD video resolution over Kramer copper cables. It is compatible with standard HDBaseT-compliant extenders at 4K@30Hz and HD video resolutions

FEATURES

High Performance Standard Extender - Professional HDBaseT extender for providing up to 200m (650ft) extended-reach video signal extension over twisted-pair copper infrastructures. TP-583Txr is a standard extender with backward HDBT compatibility, enabling it to be connected to any market-available HDBaseT-compliant extension product. It employs low-level video compression technology that delivers visually lossless performance for 4K@60 (4:4:4) and HDR signals with near-zero latency

HDMI Signal Extension - HDR HDMI 2.0 and HDCP 2.2 compliant. Supports deep color, x.v.Color™, lip sync, HDMI uncompressed audio channels, Dolby TrueHD, DTS-HD, 2K, 4K, and 3D. EDID and CEC signals are passed through from the source to the display

I-EDIDPro™ Kramer Intelligent EDID Processing™ - Intelligent EDID pass-through algorithm that ensures Plug and Play operation for HDMI source and display systems

Multi-channel Audio Extension - Up to 32 channels of digital stereo uncompressed signals for supporting studio-grade surround sound

Bidirectional RS-232 Extension - Serial interface data flows in both directions, allowing data transmission and device control

Bidirectional Infrared Extension - IR interface data flows in both directions, allowing remote control of peripheral devices located at either end of the extended line

Cost-Effective Maintenance - Status LED indicators for HDMI and HDBT ports facilitate easy local maintenance and troubleshooting. Local firmware upgrade via RS-232 connection ensures lasting, field-proven deployment

Easy Installation - Compact DigiTOOLS® fan-less enclosure for dropped-ceiling mounting, or side-by-side mounting of 3 units in a 1U rack space with the recommended rack adapter



KRAMER

TECHNICAL SPECIFICATIONS

Inputs	1 HDMI: On a female HDMI connector
Outputs	1 HDBT: On an RJ-45 connector
Ports	1 RS-232: On a 3-pin terminal block connector for serial link extension 1 IR: On a 3.5mm mini jack connector
Standard Compression Extension	Up to 100m (330ft) at 4K@60Hz (4:4:4) Up to 100m (330ft) at 4K@60Hz (4:2:0) Up to 180m (590ft) at full HD (1080p @60Hz 36bpp)
High Compression Extension	Up to 100m (330ft) at 4K@60Hz (4:4:4) Up to 180m (590ft) at 4K@60Hz (4:2:0) Up to 200m (650ft) at full HD (1080p @60Hz 36bpp) Note: When using recommended Kramer cables Standards Compliance: HDBaseT 1.0
Video	Max Data Rate: Up to 18Gbps (6Gbps per graphic channel) Standard Compression Max Resolution: 4096x2160@60Hz (4:4:4) 24bpp High Compression Max Resolution: 3840x2160@60Hz (4:4:4) 24bpp Compliance: HDMI 2.0, HDCP 2.2, HDR 10
Extended Bidirectional RS-232	300 to 115200 baud rate
Extended Bidirectional IR	20kHz to 100kHz frequency
User Interface	Indicators IN, OUT, LINK and ON LEDs Controls DIP-switches
Power	Source 12V DC, 2A Consumption 400mA
Environmental Conditions	Operating Temperature: 0° to +40°C (32° to 104°F) Storage Temperature: -40° to +70°C (-40° to 158°F) Humidity: 10% to 90%, RHL non-condensing
Regulatory Compliance (Standards Compliance)	Safety: CE, UL Environmental: RoHs, WEEE
Enclosure	Size: DigiTOOLS® Type: Aluminum Cooling: Convection ventilation
Accessories	Included: Power adapter, power cord, bracket set

PRODUCT DIMENSION: 12.00cm x 7.15cm x 2.44cm (4.72" x 2.81" x 0.96") W, D, H

PRODUCT WEIGHT: 0.3kg (0.6lbs) approx

SHIPPING DIMENSION: 15.70cm x 12.00cm x 8.70cm (6.18" x 4.72" x 3.43") W, D, H

SHIPPING WEIGHT: 0.7kg (1.4lbs) approx

