

ICRealtime ICR-D2732Z 2MP IP Indoor/Outdoor Mid Size Vandal Dome Camera/2.7-12mm Lens/98ft IR/POE

Camera	
Image Sensor	1/2.9" 2Megapixel progressive scan CMOS
Effective Pixels	1920(H) x 1080(V)
Scanning System	Progressive
Electronic Shutter Speed	Auto/Manual, 1/3(4)~1/100000s
Min. Illumination	0.01Lux/F1.4(Color); 0Lux/F1.4(IR on)
S/N Ratio	More than 50dB
Video Output	N/A
Camera Features	
Max. IR LEDs Length	98' (30m)
Day/Night	Auto(ICR)/Color/B/W
Backlight Compensation	BLC / HLC / DWDR
White Balance	Auto/Manual
Gain Control	Auto/Manual
Noise Reduction	3D
Privacy Masking	Up to 4 areas
Lens	
Focal Length	2.7mm~12mm
Max Aperture	F1.4
Focus Control	Auto
Angle of View	H: 95°~ 34°
Lens Type	Motorized/ Fixed Iris
Mount Type	Board-in Type
Video	
Compression	H.264+ / H.264
Resolution	1080P(1920x1080)/1.3M(1280x 960)/720P(1280x 720)/D1(704x 576 /704x 480)/CIF(352x 288/352x 240)
Frame Rate	1080P/720P(1 ~ 25/30fps) Sub Stream - D1/CIF(1 ~ 25/30fps)
Bit Rate	H.264: 3K ~ 8192Kbps
Audio	
Compression	N/A
Interface	N/A
Network	
Ethernet	RJ-45 (10/100Base-T)
Wi-Fi	N/A
Protocol	IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Bonjour, 802.1x
Compatibility	ONVIF, CGI
Max. User Access	20 users
Smart Phone	iPhone, iPad, Android, Windows Phone
Auxiliary Interface	
Memory Slot	Micro SD , Max 128GB
RS485	N/A
Alarm	N/A
PIR Sensor Range	N/A
General	

Power Supply	12VDC / PoE (802.3at)
Power Consumption	Max 14W
Working Environment	-30° C ~ +60° C (-22° F ~ +140° F) / Less than 95% RH
Ingress Protection	IP67
Vandal Resistance	IK10
Dimensions	122mm x 89mm
Weight	0.5Kg(1.1lb)
Adjustment axis	3-axis