

Xantech XT-HDBT-EX100-4K18G-KIT 4K60 HDR HDBaseT Extender(Transmitter/Receiver) Set with ARC/RS-232/IR/PoH (100m)

XT-HDBT-EX100-4K18G-TX Transmitter

- Video Input Connectors 1x HDMI Type A, 19-pin female
- Video Output Connectors 1x HDBaseT™ RJ45 connector
- Audio Output Connector 1x Optical (TOSLINK), 2x RCA (L/R) analog
- RS-232 serial port 1x DB-9 connector
- Ethernet ports 1x RJ45, female
- IR Input ports 1x 12V 3.5mm stereo jack
- IR Output ports 1x 12V 3.5mm mono jack

XT-HDBT-EX100-4K18G-RX Receiver

- Video Input Connectors 1x HDBaseT™ RJ45 connector
- Video Output Connectors 1x HDMI Type A, 19-pin female
- Audio Input Connector 1x Optical (TOSLINK)
- RS-232 serial port 1x DB-9 connector
- Ethernet ports 1x RJ45, female
- IR Input ports 1x 12V 3.5mm stereo jack
- IR Output ports 1x 12V 3.5mm mono jack
- Extender Dimensions (W x D x H) 148 x 129 x 22mm (with connections)
- Extender Dimensions (W x D x H) 134 x 129 x 22mm (without connections)
- Ind. Extender Weight 0.45kg (excluding accessories)
- Carton / Box Dimensions (W x D x H) 335 x 285 x 58 mm
- Shipping Weight 1.5kg
- Operating Temperature 32°F to 104°F (0°C to 40°C)
- Storage Temperature -4°F to 140°F (-20°C to 60°C)
- Power Supply 15V / 2A DC power supply, screw type connector