

# Digital Projection M-Vision WUXGA-LED 1000 Projector WUXGA 1000/10000x1 /16x10

Video & Computer			Communication & Control		
Type	Connector	Qty	Type	Connector	Qty
HDMI 1.3	HDMI	2	LAN	RJ45	1
VGA / Analog RGB	15-pin D-Sub	1	RS232 In	9-pin D Sub	1
Component Video	3 x RCA	1	RS232 Out	9-pin D Sub	1
Component Video	3 x BNC	1	IR Input	3.5mm Stereo Jack	1
S-Video	4-pin Mini DIN	1	12V Trigger	3.5mm Stereo Jack	2
Composite Video	RCA	1			

3D Formats Supported	HDTV Formats Supported
Not applicable	1080p (24Hz, 25Hz, 30Hz, 50Hz, 60Hz), 1080i (50Hz, 60Hz), 720p (50, 60Hz)
Computer Compatibility	Bandwidth
Up to 1920 x 1200	200 MHz on analog RGB
	165 Megapixels per second on HDMI
Remote Control	Automation Control
IR remote control	LAN
On-Board keypad	Daisy chain RS232 control
Lamp Type	Typical Lamp Life
LED Illumination Module	60,000 hours

Lenses			
Lens	Part No.	Focus Range	Lens Shift
0.73 fixed	110-171	0.97m - 1.3m	none
0.84 - 1.03 : 1 zoom	112-762	1.5m - 4m	Vert: 0.45 (U) 0.45 (D) frame, Hor: 0.12 (L) 0.12 (R) frame
1.56 - 1.86 : 1 zoom	110-157	2m - 7m	Vert: 0.6 (U) 0.6 (D) frame, Hor: 0.15 (L) 0.15 (R) frame
1.85 - 2.4 : 1 zoom	110-172	2.5m - 10m	Vert: 0.6 (U) 0.6 (D) frame, Hor: 0.15 (L) 0.15 (R) frame
2.4 - 4.0 : 1 zoom	112-319	4m - 12m	Vert: 0.6 (U) 0.6 (D) frame, Hor: 0.15 (L) 0.15 (R) frame
Lens Mount			
Manual shift, zoom & focus.			

Mechanical Mounting	
Front/Rear Table	
Front/Rear Ceiling	
Adjustable Front/Rear Feet	
Power Requirements	Power Consumption
100-240VAC 50/60Hz single phase	330W
Thermal Dissipation	Fan Noise
1126 BTU/Hour	30 dBA
Operating/Storage Temperature	Operating Humidity
Operating: 10 to 40C (50 to 95F) Storage: -20 to 60C (-4 to 140F)	20% to 85% non condensing
Weight (Chassis Only)	Dimensions
15 kg 33.1 lb	L: 41.8 cm W: 44.7 cm H: 18.2cm L: 16.5 in W: 17.6 in H: 7.2 in