

# Ashly ne4250.70 4 x 250W/70V Network Power Amplifier/Constant Voltage with Selectable High-Pass Filter

This listing is for ne4250.70 Amplifier only. Use description below as a general reference.

These NE Series Amplifiers are uniquely designed around an energy efficient Class- D platform with a switching power supply.

Connecting and controlling an amplifier for networked systems has now been simplified with Network-Enabled Amplifiers. This line offers ease of use, setup and control using standard 10/100 Ethernet protocol and Protea™ ne Software. No special outboard control units are needed. Choose either 4-channel ne4250 or 8-channel ne8250 amplifiers are rated at 250W per channel with separate HI-Z and LO-Z models.

ne Series amplifiers are offered in two separate platforms—the standard network amplifier or a network amplifier with an on-board Protea™ DSP Processor. Each can be customized for any installation by adding your choice of AES3 inputs, Dante™ or CobraNet™ card.

NE Multi-Channel amplifiers are also offered with 240V Line Voltage in either Low- Z or 100V constant voltage output models for International customers.

## Power Ratings

Continuous Average Power Output: Per Channel, All Channels Driven

| 4-Ch Model | Panel Views | 4Ω   | 8Ω   | 8Ω (br) | 25V* | 70V* | 100V* |
|------------|-------------|------|------|---------|------|------|-------|
| ne 4250    | Front Rear  | 250W | 150W | 500W    | —    | —    | —     |
| ne 4250.25 | —           | —    | —    | —       | 250W | —    | —     |
| ne 4250.70 | —           | —    | —    | —       | —    | 250W | —     |
| ne 4250.10 | —           | —    | —    | —       | —    | —    | 250W  |
| 8-Ch Model | Panel Views | 4Ω   | 8Ω   | 8Ω (br) | 25V* | 70V* | 100V* |
| ne 8250    | Front Rear  | 250W | 150W | 500W    | —    | —    | —     |
| ne 8250.25 | —           | —    | —    | —       | 250W | —    | —     |
| ne 8250.70 | —           | —    | —    | —       | —    | 250W | —     |
| ne 8250.10 | —           | —    | —    | —       | —    | —    | 250W  |

\* Must be ordered as separate 25V, 70V, or 100V constant voltage models.