

Soundtube IW31-EZ-WH 3in PREMIUM FULL-RANGE IN-WALL SPEAKER/190Hz-14kHz/White

System Type	3-inch full-range, h-wal (10-watt transformer or 25/70.7/100-vott or transformer bypass)
Impedance {nominal)1	8 ohm
Sensitivity dB @ 2.83 V/1 m	85.5 dB
Sensitivity dB @ 1 W/1 m 2	85.5 dB
Frequency Response (- 3 dB)3	190 Hz -14 kHz
Frequency Response (-10 dB)3	115 Hz-22 kHz
Max. Program Power 4	40 W
Max. Continuous Power RMS 5	20 W
Max. Power SPL @ 1 m 6	98.5 dB
Coverage Angle (-6 dB <& 2 kHz)	'H0°
Coverage Angle (-6 dB @ 10 kHz)	45°
Coverage Angle (averaged from 2 to 10 kHz)	120°
Directivity Factor (Q)	4.5 (averaged 100Hz - 10kHz). 2.8 (2kHz)
Directivity Index (DI) dB	5.5 (averaged 100Hz - 1CkHz). 4.4 (2kHz)
Tap Selector (transformer accessory only)	Sw-posrtion rotary switch or transformer bypass
Transducer - Full-Range Driver	76.1 mm (3.0 in.) Polypropylene driver with butyl rubber surround
Low Frequency Voice Coil	19.0mm (0.75 in.)
Enclosure Material	ABS baffle, steel backcan
Gnle	Corrosion-resistant. pov,'der-ooaled aluminum
Inputs	Hardwrelead
Colors	White
Back can Height	889 mm (3.50 in.)
Visible Height	127.0 mm (5.00 in.)
Vfeible Width	127.0 mm (5.00 in.)
Weight	1.4 kg (3 lbs.)
Shipping Weight	1.8 kg (4 lbs.)
Packaging	One per box
Included Accessories	Conduit connector, paint mask and wire nuts
Optional Accessories	Pre-construction bracket (AC-IW3-PCB), Theft-resistant stainless steel grille (AC-IW3-TRG), 10-inch powered subwoofer (SM1001p)
Regulatory - UL	UL 1480 (UEAY) and 2043 approved
Regulatory - CE	Approved
RoHS	Approved