

PreSonus Studio 26c 2X4 UHD USB-C Audio Interface with 2 Mic Inputs/24-bit/192kHz

General	
Sample Rates	44.1, 48, 88.2, 96, 176.4, or 192 kHz
Converter Resolution	24 bit
Converter Dynamic Range	114 dB
Converter Dynamic Range	114 dB
Microphone Inputs	
Maximum Level	+4.5 dBu (balanced, min gain)
Gain Range	70 dB
Frequency Response	20 Hz - 20 kHz (± 0.1 dB, min gain, 48 kHz)
Dynamic Range	110 dB (A-wtd, min gain)
THD + N	0.004% (1 kHz, -1 dBFS, unity gain)
EIN	-125 dBu (max gain, 150 Ω , A-wtd)
Input Impedance	1.6 k Ω
Phantom Power	+48 VDC (10 mA total)
Line Inputs	
Maximum Level	+19.5 dBu (balanced, min gain)
Gain Range	70 dB
Frequency Response	20 Hz - 20 kHz (± 0.1 dB, min gain, 48 kHz)
Dynamic Range	110 dB (A-wtd, min gain)
THD + N	0.007% (1 kHz, -1 dBFS, min gain)
Input Impedance	10 k Ω
Instrument Inputs	
Maximum Level	+14 dBu (unbalanced, min gain)
Gain Range	70 dB
Frequency Response	20 Hz - 20 kHz (± 0.15 dB, 48 kHz, min gain)
Dynamic Range	110 dB (A-wtd, min gain)
THD + N	0.008% (1 kHz, -1 dBFS, min gain)
Input Impedance	1 M Ω
Line Outputs (Mains)	
Type	$\frac{1}{4}$ " TRS Female, DC Coupled*
Maximum Level	+10 dBu (balanced)
Frequency Response	20 Hz - 20 kHz (± 0.1 dB, unity gain, 48 kHz)
Dynamic Range	108 dB (A-wtd)
THD + N	0.0015% (1 kHz, -1 dBFS)
Line Outputs (3/4)	
Type	$\frac{1}{4}$ " TRS Female, DC Coupled*
Maximum Level	+10 dBu (balanced)
Frequency Response	20 Hz - 20 kHz (± 0.1 dB, unity gain, 48 kHz)
Dynamic Range	113 dB (A-wtd)
THD + N	0.008% (1 kHz, -1 dBFS)
Headphone Outputs	
Maximum Power	30 mW/channel (56 Ω load)
Frequency Response	20 Hz - 20 kHz (± 0.2 dB, 56 Ω load, 48 kHz)

Dynamic Range	104 dB (A-wtd, 56Ω load)
THD + N	0.009% (1 kHz, -1 dBFS, no load)
Impedance Working Range	32Ω to 300Ω
Physical	
Height	1.75" (44 mm)
Width	7" (180 mm)
Depth	5.5" (144 mm)
Weight	1.6 lbs. (0.7 kg)