

Soundtube FP6030-II-BK Twin 1 inch Sound-Focusing Speaker/130Hz-22kHz/Black

Nominal Impedance	8 ohm
Impedance (min)	5.4 ohm
Sensitivity dB @ 2.83V/1M	75.0dB
Sensitivity dB @ 1W/1M (2)	75.0dB
Frequency Response (± 3 dB)	170 Hz – 22 kHz (300 Hz with high-pass filter)
Frequency Response (± 10 dB)	130 Hz – 22 kHz (200 Hz with high-pass filter)
Max. Program Power	30w
Max. Continuous Power RMS	15w
Max. Power SPL @ 1 M	87.0dB
Tap Selector	Optional j-box transformer with 4 position rotary switch
70.7 Volt Transformer Taps	10w / 85.0dB
100 Volt Transformer Taps (dB)	10w / 85.0dB
25 Volt Transformer Taps (dB)	1.25w / 76.0dB
Transformer Options	25 / 70.7 / 100 Volt option with a 8 Ohm direct
Transducer - Full-Range Driver	2 x 1 in (25 mm) aluminum, high excursion
Coverage Angle (-6 dB @ 2 kHz) raw	65
Angle	65
Inputs	4.6m (15') hardwire lead
Height (SM = Height)	332.7 mm / 13.10 in
Diameter (SM = Width)	781.1 mm / 30.75 in
Weight	2.5 kg / 5.5 lbs
Shipping Weight	5 kg / 11.0 lbs
Accessories Optional	AC-CFP Custom-Printed SoundSleeve™, AC-WB4 Wall-Mount Bracket, AC-JB10- XFMR & AC-JB20-XFMR, AC-FP6-RMA Rigid-Mount Adaptor
Packaging	1 per box
Regulatory - CE	approved
Regulatory - RoHS	approved
Regulatory - CCC	approved