

Soundtube RS4-EZ 4 inch Full-Range Open-Ceiling Speaker

System Type	4" Full range, open-ceiling, ported (20 Watt transformer for 25/70.7/100 Volt or voice coil direct)
Nominal Impedance	8 ohm
Impedance (minimum)	6.9 ohm
Sensitivity dB @ 2.83V/1M	90.0dB
Sensitivity dB @ 1W/1M (2)	90.0dB
Frequency Response (± 3 dB)	185 Hz - 13 kHz
Frequency Response (± 10 dB)	98 Hz - 22 kHz
Max. Program Power	40w
Max. Continuous Power RMS	20w
Max. Power SPL @ 1 M	103.0dB
Tap Selector	5 Position rotary switch with transformer bypass
70.7 Volt Transformer Taps	20w / 103.0dB
100 Volt Transformer Taps (dB)	20w / 103.0dB
25 Volt Transformer Taps (dB)	2.5w / 94.0dB
Transformer Options	25 / 70.7 / 100 Volt option with a 8 Ohm direct
Colors	Black or white
Port length	2.84 in
Tweeter - part	4" Extended-Range Paper Cone
Woofer - part	4" Full-Range
Inputs	4 Pin, 5.08 mm Euroblock for individual or daisy chain connection
Height (SM = Height)	223.5 mm / 8.79 in
Diameter (SM = Width)	195.6 mm / 7.70 in
Weight	1.8 kg / 3.96 lb
Shipping Weight	2.7 kg / 5.95 lb
Accessories Optional	Surface-Mount Bracket (AC-RS-SM5), Split Loom Tubing (AC-SLT-10), bracket for surface mount applications (AC-RS-SM5), Hanging Kit (AC-RS-HH- 10), Hanging Kit (AC-RS-HH-20), Hanging Kit (AC-RS-HH-50), Forged Eyebolt (AC-FE1), Snap Link (AC-SL-1)
Packaging	1 per box
Regulatory - UL	not planned
Regulatory - CE	Approved
Regulatory - IP	not planned

