

**Soundtube RS4-EZ-BK 4in Full-Range Open-Ceiling Speaker/185 Hz - 13 kHz/Black**

System Type	4-inch, full-range, open-ceiling, ported (20-watt transformer for 25/70.7/100-volt or transformer bypass)
Impedance (nominal)1	8 ohms
Sensitivity dB @ 2.83 V/l m	90.0 dB
Sensitivity dB @ 1 W/l m?	90.0 dB
Frequency Response {- 3 dB)3	185 Hz-13 kHz
Frequency Response {-10 dB)3	98 Hz-22 kHz
Max. Program Power-1	40 W
Max. Continuous Power RMS5	20 W
Max. Power SPL @ 1 m6	103.0 dB
Coverage Angle (-6 dB @ 2 kHz)	160°
Coverage Angle (-6 dB @ 10 kHz)	60°
Coverage Angle (averaged 2-10 kHz)	95°
Directivity Factor (Q)	4.3 (averaged 100 Hz -10 kHz); 3.8 (2 kHz)
Directivity Index (CH)	4.9 dB (averaged 100 Hz -10 kHz); 5.8 dB (2 kHz)
Tap Selector	Five-position rotary switch with transformer bypass position
Transducer - Full-Range Driver	102 mm (4.0 in.) Paper cone, treated cloth surround
Voice Coil	20.0 mm (0.79 in.)
Enclosure Material	Injection molded ABS, glass fiber reinforced
Grille	Steel with powder-coat finish
Inputs	Four-pin, 5.08 mm Euroblock for individual or daisy chain connection
Colors	Black or white (paintable)
Height	223.5 mm (8.80 in.)
Diameter	195.6 mm (A/0 in.)
Weight	1.8 kg (3.9 lbs.)
Shipping Weight	2.7 kg (6 lbs.)
Packaging	One per box
Included Accessories	Hanging hardware, Euroblock connector and terminal weather boot
Optional Accessories	Surface-mount bracket (AC-RS-SM5)
Regulatory - UL	UL 2239 (hanging cable) approved
Regulatory - CE	Approved
RoHS	Approved