

Soundtube RF-41-20-SO Rf-41-20 Speaker and Baffle Only/No Grille

Nominal Impedance	8 ohm
Impedance (min)	6.6 ohm
Sensitivity dB @ 2.83V/1M	88.5dB
Sensitivity dB @ 1W/1M (2)	88.5dB
Frequency Response (± 3 dB)	155 Hz - 22 kHz
Frequency Response (± 10 dB)	71 Hz - 22 kHz
Max. Program Power	40W
Max. Continuous Power RMS	20W
Max. Power SPL @ 1 M	101.5dB
Directivity Factor (Q) (Averaged 100Hz - 10kHz, @ 2kHz)	4.9 (Average 100 Hz - 10 kHz) 4.6 (2 kHz)
Directivity Index (DI) dB (Averaged 100Hz - 10kHz, @ 2kHz)	5.7dB (Average 100 Hz - 10 kHz) 6.6dB (2 kHz)
Tap Selector	5 Position rotary switch with transformer bypass
70.7 Volt Transformer Taps	20w / 101.5dB
100 Volt Transformer Taps (dB)	20w / 101.5dB
25 Volt Transformer Taps (dB)	2.5w / 92.5dB
Transformer Options	25 / 70.7 / 100 Volt option with a 8 Ohm direct - .31 W – 20 W
Transducer - Full-Range Driver	4" Treated Fiber Cone w/ Cloth Surround
Angle	145°
Colors	White
Inputs	Spring terminals
Backcan Diameter	209.8 mm / 8.3 in
Backcan Height	62.5 mm / 2.5 in
Visible Diameter	320 mm / 12.6 in
Visible Height	6.4 mm / 0.3 in
Weight	1.6 kg / 3.5 lb
Shipping Weight	1.8 kg / 4.0 lb
Packaging	1 per box
Regulatory - UL	not planned
Regulatory - CE	Approved
Regulatory - RoHS	approved
Regulatory - IP	not planned