

Soundtube RS42-EZ 4 inch Open-Ceiling Speaker

System Type	4.0" Coax, open-ceiling, ported (20 Watt transformer for 25/70.7/100 Volt or voice coil direct)
Nominal Impedance	16 ohm
Impedance (minimum)	16.0 ohm
Sensitivity dB @ 2.83V/1M	84.0dB
Sensitivity dB @ 1W/1M (2)	87.0dB
Frequency Response (± 3 dB)	140 Hz - 22 kHz
Frequency Response (± 10 dB)	100 Hz - 22 kHz
Max. Program Power	40w
Max. Continuous Power RMS	20w
Max. Power SPL @ 1 M	100.0dB
Tap Selector	6 Position rotary switch with transformer bypass
70.7 Volt Transformer Taps	20w / 100.0dB
100 Volt Transformer Taps (dB)	20w / 100.0dB
25 Volt Transformer Taps (dB)	2.5w / 91.0dB
Transformer Options	25 / 70.7 / 100 Volt option with a 16 Ohm direct
Colors	Black or white
Tweeter - part	19mm (0.75in) Silk dome w/ BroadBeam Ring™
Woofer - part	4" Polypropylene Cone with Butyl Rubber Surround
Inputs	4 position ceramic terminal connector
Height (SM = Height)	199.6 mm / 7.85 in
Diameter (SM = Width)	189.5 mm / 7.46 in
Carton length	241.3 mm / 9.50 in
Weight	1.4 kg / 3.08 lb
Shipping Weight	1.8 kg / 3.96 lb
Accessories Optional	Beam Clamp (AC-BC-1), Split Loom Tubing (AC-SLT-10), Hanging Kit (AC-RSEZ-HH-10), Hanging Kit (AC-RSEZ-HH-20), 50' Hanging Kit (AC-RSEZ-HH-50), Forged Eyebolt (AC-FE1), Snap Link (AC-SL-1)
Packaging	1 per box
Regulatory - UL	1480 planned
Regulatory - CE	Approved
Regulatory - IP	not planned
Regulatory - CCC	approved