

Soundtube SM1001p-WH HIGH-POWERED SURFACE-MOUNT SUBWOOFER/42 Hz-110 Hz/White

| | |
|--|---|
| System Type | 10-inch active woofer with a 10 inch passive radiator |
| Impedance (nominal) | N/A (powered) |
| Sensitivity dB @ 2.83 V/1 m | 92 dB |
| Sensitivity dB @ 1 W/1 m 1 | 92 dB |
| Frequency Response (-3 dB) ² | 55 Hz-118 Hz |
| Frequency Response (-10 dB) ² | 41 Hz - 224 Hz |
| Max. Program Power ³ | 300 W |
| Max. Continuous Power RMS ⁴ | 200 W |
| Max. Power SPL @ 1 m ⁵ | 111.0 dB |
| Low-Frequency Transducers | One active 254 mm (10 in.) polypropylene cone with butyl rubber surround, one passive 254 mm (10 in.) polypropylene cone with butyl rubber surround |
| Low-Frequency Voice Coil | 35.0 mm (1.38 in.) |
| Crossover Frequency | Variable, user-selectable 50 Hz thru 200 Hz |
| High Pass Output Filter | Variable, user-selectable 50 Hz thru 200 Hz |
| Enclosure Material | MDF with plywood top and back |
| Input | Balanced XLR |
| Output | Balanced XLR |
| Color Options | Black or white, custom colors available. |
| Height (excluding feet) | 355.6 mm (14.0 in.) |
| Width | 324.6 mm (24.6 in.) |
| Depth (excluding SM bracket) | 364.7 mm (14.4 in.) |
| Weight | 12.3 kg (27 lbs.) |
| Shipping Weight | 14.5 kg (32 lbs.) |
| Packaging | One per box |
| Included Accessories | Safety cable, forged eyebolt |
| Optional Accessories | Surface mount bracket, corner mount bracket |
| Regulatory - CE | Approved |
| RoHS | Approved |