

## Soundtube IPD-RS82-EZ BK 8 inch Coax Open-Ceiling Network Speaker/Black

Frequency Response ( $\pm 3$ dB)	100 Hz - 22kHz
Frequency Response ( $\pm 10$ dB)	80 Hz - 22 kHz
Max. Power SPL @ 1 M	103 dB
Directivity Factor (Q) (Averaged 100Hz - 10kHz, @ 2kHz)	6.7 (Average 100Hz - 10 kHz) 6.0 (2 kHz)
Directivity Index (DI) dB (Averaged 100Hz - 10kHz, @ 2kHz)	6.7db (Average 100 Hz - 10 kHz) 7.8dB (2 kHz)
Total Bi-Amp Power	40 W
Color	Black
Connections	RJ45 ethernet connector
Height (SM = Height)	327.7 mm / 10.4 in
Diameter (SM = Width)	256.0 mm / 12.9 in
Weight	5.0 kg / 11.0 lbs
Shipping Weight	5.9 kg / 9.0 lbs
Accessories Optional	Beam Clamp (AC-BC-1), Split Loom Tubing (AC-SLT-10), Hanging Kit (AC-RSEZ-HH-10), Hanging Kit (AC-RSEZ-HH-20), 50' Hanging Kit (AC-RSEZ-HH-50), Forged Eyebolt (AC-FE1), Snap Link (AC-SL-1)