

## Soundtube RS62-EZ 6.5 inch Open-Ceiling Speaker

System Type	6.5" Coax, open-ceiling, ported (32 Watt transformer for 25/70.7/100 Volt or voice coil direct)
Nominal Impedance	16 ohm
Impedance (minimum)	16.0 ohm
Sensitivity dB @ 2.83V/1M	86.0dB
Sensitivity dB @ 1W/1M (2)	89.0dB
Frequency Response ( $\pm$ 3 dB)	100 Hz - 22 kHz
Frequency Response ( $\pm$ 10 dB)	80 Hz - 22 kHz
Max. Program Power	64w
Max. Continuous Power RMS	32w
Max. Power SPL @ 1 M	104.0dB
Tap Selector	6 Position rotary switch with transformer bypass
70.7 Volt Transformer Taps	32w / 104.0dB
100 Volt Transformer Taps (dB)	32w / 104.0dB
25 Volt Transformer Taps (dB)	4w / 95.0dB
Transformer Options	25 / 70.7 / 100 Volt option with a 16 Ohm direct
Colors	Black or white
Tweeter - part	1" Silk dome w/ BroadBeam Ring™
Woofers - part	6.5" Polypropylene Cone with Butyl Rubber Surround
Inputs	4 position ceramic terminal connector
Height (SM = Height)	264.2 mm / 10.40 in
Diameter (SM = Width)	256 mm / 10.07 in
Carton length	304.8 mm / 12.00 in
Weight	2 kg / 4.40 lb
Shipping Weight	2.7 kg / 5.95 lb
Accessories Optional	Beam Clamp (AC-BC-1), Split Loom Tubing (AC-SLT- 10), Hanging Kit (AC-RSEZ-HH-10), Hanging Kit (AC-RSEZ-HH-20), 50' Hanging Kit (AC-RSEZ-HH-50), Forged Eyebolt (AC- FE1), Snap Link (AC-SL-1)
Packaging	1 per box
Regulatory - UL	1480 planned
Regulatory - CE	Approved
Regulatory - RoHS	approved
Regulatory - IP	not planned
Regulatory - CCC	approved