

Soundtube SM1001p-BK HIGH-POWERED SURFACE-MOUNT SUBWOOFER/42 Hz-110 Hz/Black

System Type	10-inch active woofer with a 10 inch passive radiator
Impedance (nominal)	N/A (powered)
Sensitivity dB @ 2.83 V/1 m	92 dB
Sensitivity dB @ 1 W/1 m 1	92 dB
Frequency Response (-3 dB) ²	55 Hz-118 Hz
Frequency Response (-10 dB) ²	41 Hz - 224 Hz
Max. Program Power ³	300 W
Max. Continuous Power RMS ⁴	200 W
Max. Power SPL @ 1 m ⁵	111.0 dB
Low-Frequency Transducers	One active 254 mm (10 in.) polypropylene cone with butyl rubber surround, one passive 254 mm (10 in.) polypropylene cone with butyl rubber surround
Low-Frequency Voice Coil	35.0 mm (1.38 in.)
Crossover Frequency	Variable, user-selectable 50 Hz thru 200 Hz
High Pass Output Filter	Variable, user-selectable 50 Hz thru 200 Hz
Enclosure Material	MDF with plywood top and back
Input	Balanced XLR
Output	Balanced XLR
Color Options	Black or white, custom colors available.
Height (excluding feet)	355.6 mm (14.0 in.)
Width	324.6 mm (24.6 in.)
Depth (excluding SM bracket)	364.7 mm (14.4 in.)
Weight	12.3 kg (27 lbs.)
Shipping Weight	14.5 kg (32 lbs.)
Packaging	One per box
Included Accessories	Safety cable, forged eyebolt
Optional Accessories	Surface mount bracket, corner mount bracket
Regulatory - CE	Approved
RoHS	Approved