

Soundtube RS82-EZ 8 inch Open-Ceiling Speaker

System Type	8.0" Coax, open-ceiling, ported (64 Watt transformer for 25/70.7/100 Volt or voice coil direct)
Nominal Impedance	16 ohm
Impedance (minimum)	16.0 ohm
Sensitivity dB @ 2.83V/1M	89.0dB
Sensitivity dB @ 1W/1M (2)	92.0dB
Frequency Response (± 3 dB)	100 Hz - 22 kHz
Frequency Response (± 10 dB)	80 Hz - 22 kHz
Max. Program Power	128w
Max. Continuous Power RMS	64w
Max. Power SPL @ 1 M	110.0dB
Tap Selector	6 Position rotary switch with transformer bypass
70.7 Volt Transformer Taps	64w / 110.0dB
100 Volt Transformer Taps (dB)	64w / 110.0dB
25 Volt Transformer Taps (dB)	8w / 101.0dB
Transformer Options	25 / 70.7 / 100 Volt option with a 16 Ohm direct
Colors	Black or white
Tweeter - part	1" Silk dome w/ BroadBeam Ring™
Woofer - part	8" Polypropylene Cone w/ Butyl Rubber Surround
Inputs	4 position ceramic terminal connector
Height (SM = Height)	327.7 mm / 12.90 in
Diameter (SM = Width)	325.9 mm / 12.83 in
Carton length	381 mm / 15.00 in
Weight	3.6 kg / 7.93 lb
Shipping Weight	4.5 kg / 9.92 lb
Accessories Optional	Beam Clamp (AC-BC-1), Split Loom Tubing (AC-SLT-10), Hanging Kit (AC- RSEZ-HH-10), Hanging Kit (AC-RSEZ-HH-20), 50' Hanging Kit (AC-RSEZ- HH-50), Forged Eyebolt (AC-FE1), Snap Link (AC-SL-1)
Packaging	1 per box
Regulatory - UL	1480 planned
Regulatory - CE	Approved
Regulatory - IP	not planned
Regulatory - CCC	approved