



### Description:

The CI150 features three 6.5" RPF flat-piston Fiberglass & Kevlar composite cone woofers that deliver true high-efficiency and performance across the operating bandwidth.

The 1" variable axis tweeter allows high frequencies to be directed to the listener in situations where placement is less than optimal.

Additionally, the Positive Clamping System ensures accurate control of low end performance and clear reproduction of the sound into the listening space.

### Features:

- Three 5.25 inch RPF flat-piston fiberglass & Kevlar composite woofers with butyl rubber surrounds and two 1 inch tweeters
- Eliminates the need for a separate center channel
- Limited Lifetime Warranty
- Auto-Reset Overload Protection
- Absolute Phase Crossover Network
- Magnetic Micro-Flange Grille
- Positive Clamping System for a tight, non-resonant seal
- Unicell Acoustic Treatment for tweeter diffraction prevention

### Applications:

Engineered for home theater or distributed audio applications where high-efficiency, added bass response and rapid installation are critical. The CI150 pairs with Premier Collection's PC1.5 and PC33.5. Use CI-SURRX or CI6.2X for surround speakers.

### Warranty Information:

The CI150 comes with a limited lifetime warranty. Products not sold through an authorized dealer/distributor will not be supported by the factory warranty. Warranties are non-transferable.

### Phase Technology:

8005 W 110th St  
Suite 208  
Overland Park, KS 66102  
Phone: 913.663.5600  
Toll Free: 855.663.5600  
Fax: 913.663.3200  
www.phasetech.com

### CI150 PRODUCT SPECIFICATIONS

NOMINAL IMPEDANCE	4Ω
SENSITIVITY dB @ 2.83V/1M	90 dB
FREQUENCY RESPONSE	55 Hz - 22 kHz
RECOMMENDED POWER	15 - 150 Watts
TWEETER	(2) 1" (25.4 mm) Variable Axis Soft Dome w/ Unicell Acoustic Treatment
MIDRANGE	N/A
WOOFER	(3) 5.25" RPF Flat-Piston Fiberglass & Kevlar Composite w/ NBR Surround
ENCLOSURE TYPE	Sealed
INPUTS	Screw Terminals
GRILLE	White Powder-Coated Galvanized Steel (paintable)
DIMENSIONS	31.375" H x 8.125" W x 4.25" D
CUTOUT DIMENSIONS	30.375" H x 7" W
MOUNTING DEPTH	3.875"
WEIGHT	18.5 lbs
SHIPPING WEIGHT	22 lbs
OPTIONAL ACCESSORIES	Rough-In Bracket (RB-19)
REGULATORY - CE	Approved
RoHS	Approved