

ClearView PhoenixPlus-08 8 Channel NVR 5 Megapixel NVR with 8 PoE Port

System	
Main Processor	Dual-core embedded processor
Operating System	Embedded LINUX
Video & Audio	
IP Camera Input	8 channel
Two-way Talk	1channel Input, 1channel Output, RCA
Display	
Interface	1 HDMI,1 VGA
Resolution	1920×1080, 1280×1024, 1280×720, 1024×768
Display Split	1/4/8/9
OSD	Camera title, Time, Video loss, Camera lock, Motion detection, Recording
Recording	
Compression	H.264/MJPEG
Resolution	5Mp(2560×1920) / 3Mp(2048×1536) / 1080P(1920×1080) / 720P(1280×720) / D1 (704×576/704×480)
Record Rate	80Mbps
Bit Rate	48~ 8192kbps
Record Mode	Manual, Schedule(Regular(Continuous), MD, Alarm), Stop
Record Interval	1~120 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec
Video Detection	
Trigger Events	Recording, PTZ, Tour, Alarm, Video Push, Email,FTP, Buzzer & Screen tips
Video Detection	Motion Detection,MD Zones: 396(22×18), Video Loss & Camera Blank
Playback & Backup	
Sync Playback	1/4/8
Search Mode	Time/Date, Alarm, MD & Exact search (accurate to second), Smart search
Playback Function	Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup selection, Digital zoom
Backup Mode	USB Device/Network/Internal SATA burner
Network	
Ethernet	1 RJ-45 port (10/100Mbps)
PoE	8 ports (IEEE802.3af/at)
Network Function	HTTP, TCP/IP, IPv4/IPv6, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPOE, DDNS, FTP, Alarm Server, IP Search(Support CV IP camera, DVR, NVS and etc.),SNMP, P2P
Max.User Access	128users
Smart Phone	iPhone, iPad, Android
Storage	
Internal HDD	1 SATA port, up to 6TB
Auxiliary Interface	
USB	2 ports, USB2.0
General	
Power Supply	DC48V/2A
Power Consumption	NVR: 12W(without HDD)
PoE:	Max 25.5W for single port
Working Environment	-10°C~+55°C / 10%~90%RH / 86~106kpa
Dimension (W×D×H)	Smart 1U, 270mm×205mm×45mm

Weight	0.6~0.7KG (without HDD)
--------	-------------------------